



ITEM	PART	DESCRIPTION
A	USB-C male	Connector
B	USB-C male	Connector
A + B	Connector type	USB-C male
	Contacts	Nickel plated
	Hood	Black PVC
	E-marker	No
C	Shielding	Braid
	Cable colour	Black
	Outer jacket	PVC
		Nylon braided sleeve
	Wire gauge	23 AWG + 30 AWG
	Outer diameter	∅3.5 mm
	Bend radius	minimum 14mm
Conductive Resistance	2 ohms MAX	
Insulation Resistance	10M ohm MIN.	

WIRE CONNECTION TABLE		
P1	COLOR	P2
SHELL	Black + Braid	SHELL
A1,B1,A12,B12		A1,B1,A12,B12
A5	Blue	A5
A6	Green	A6
A7	White	A7
A4,B4,A9,B9	Red	A4,B4,A9,B9

Item No.	Length	Max. Power
AC3096	1m	60W



Drawn by : EP

AC3902 USB 2.0 charging/data cable C male - C male 1 meter, nylon

Revision : 01

Date : 15-10-2025

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.