



6	PCB'A	AC6010 - SB 2.0 booster, 10 meter PCB	pcs	
5	OUTER MOLD	40P PVC, Color: Black		
4	INNER MOLD	LD PE		
3	CONNECTOR	USB2.0 ( "A" ) Female Insulation Color White Pin Gold Plated Terminal Shell Nickel Plated (with iron shell jacket)	pcs	
2	CONNECTOR	USB2.0 ( "A" ) Male Solder Type Insulation Color White Pin Gold Plated Terminal Shell Gold Plated	pcs	
1	CABLE	USB2.0 28AWG*1P+22AWG*2C+AL+D+B, OD: 4.7±0.15mm, Color: Black	mm	10000
NO.	NAME	DESCRIPTION	UNIT	Q'TY

<b>ACT</b>		
	ITEM NO.: AC6010 - USB 2.0 booster, 10 meter	
REV: A/1		
UNIT: mm		CHECKED BY: EP
SCALE: NONE		

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.