


ITEM	PART	DESCRIPTION
USB-C	USB-C male	Source connector
	Connector type	USB-C male
	Contacts	Gold plated
	Hood	Black PVC
HDMI	Shield type	Gold plated
	HDMI male	Display connector
	Connector type	USB-C male
	Contacts	Gold plated
	Hood	Black ABS + PVC
CABLE	Shield type	Gold plated
	Cable colour	Black
	Outer jacket	PVC
	Wire gauge	34 AWG
	Outer diameter	Ø4.5 ±0.3mm
	A	34 AWG TC + Drain
	B	34 AWG TC
	C	26 AWG TC
	Max. resolution @ 30Hz	3840 x 2160 (4K)
	Max. resolution @ 60Hz	4096 x 2160 (4K)
	Chroma sampling	RGB: 4:4:4
		YCbCr: 4:4:4, 4:2:2, 4:2:0



COLOR CODE

1. WHITE * BROWN
2. WHITE * RED
3. WHITE * GREEN
4. WHITE * BLUE
5. WHITE * YELLOW
6. YELLOW
7. BLUE
8. GREEN
9. WHITE
10. BLACK
11. RED

Features	
HDMI compliant:	HDMI 2.0b up to 6Gbps
DP Compliant:	DP 1.2 up to 5.4Gbps
HDR	Per HDMI 2.0b
HDCP	up to HDCP 2.2
LPCM	up to 8-ch Audio
Chipset	CS5265

ACT

Drawn by : MR

AC7315 USB-C to HDMI cable 2 meters

Revision : 02

Date : 10-02-2025

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.