ACT Connectivity Solutions – Koolhovenstraat 1E – 3772MT – Barneveld – The Netherlands





ITEM	PART	DESCRIPTION
P1	USB-C male	Connector (straight)
P2	USB-C male	Connector (Left/Right angled)
P1 + P2	Connector type	USB-C male
	Contacts	Nickel plated
	Hood	Black PVC
	E-marker	No
	Shielding	Aluminium Mylar
Cable Specs	Cable colour	Black
	Outer jacket	PVC
	Wire gauge	32, 24
	Outer diameter	Ø4.8 mm
	Bend radius	72mm
	Conductive Resistance	3 ohms MAX
	Insulation Resistance	5M ohm MIN.
USB Specs	Max. bandwidth	up to 10Gbps
	PD profiles	5, 9, 12, 15, 20 up to 3A
	Max. PD	60W
	DP-Alt mode	Yes
	Max. resolution @ 30H	4096 x 2160 (4K)
	Max. resolution @ 60H	4096 x 2160 (4K)
	Thunderbolt support	No

Item No.	Length	Max. PD
AC7405	0.5m	60W

AC7405 USB-C male (straight) to USB-C male (left or right angled) 0.5m

Revision : 01

Date : 23-05-2025

Drawn by : MR

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.