



Item No.	Length	Max. PD
AC7407	2m	60W

ITEM	PART	DESCRIPTION
P1	USB-C male	Connector (straight)
P2	USB-C male	Connector (Left/Right angled)
P1 + P2	Connector type	USB-C male
	Contacts	Nickel plated
	Hood	Black PVC
	E-marker	No
Cable Specs	Shielding	Aluminium Mylar
	Cable colour	Black
	Outer jacket	PVC
	Wire gauge	30
	Outer diameter	∅5.0 mm
USB Specs	Bend radius	75mm
	Conductive Resistance	3 ohms MAX
	Insulation Resistance	5M ohm MIN.
	Max. bandwidth	up to 10Gbps
	PD profiles	5, 9, 12, 15, 20 up to 3A
	Max. PD	60W
	DP-Alt mode	Yes
Thunderbolt support	Max. resolution @ 30Hz	4096 x 2160 (4K)
	Max. resolution @ 60Hz	4096 x 2160 (4K)
	Thunderbolt support	No

ACT

Drawn by : FV

AC7407 USB-C male (straight) to USB-C male (left or right angled) 2m

	Revision : 01
Date : 15-10-2025	

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.