



ITEM	PART		DESCRIPTION
A + B	Connector type	HDMI A male	
	Contacts	Gold plated	
	Hood	Molded plastic	
	Shield type	Aluminum Mylar	
	Conductor material	Copper	
	Cable colour	Black	
C	Outer jacket	PVC	
	Wire gauge	28 AWG	
	Outer diameter	Ø7.3 ±0.2mm	
	Bend radius	40mm	
	Temperature range	-20°C to +70°C (+5%)	
	Humidity range	45% to 65%	
	Max. bandwidth	18 Gb/s	
	HDMI version	2.0	
	HDMI standard	HDMI High Speed	
	Max. resolution @ 60Hz	3840 x 2160 (4K)	
	Chroma sampling	4:2:0	
	Colour bit depth	8 bits per colour	
D	Protective cap	PE	



Drawn by : EP

7 meters High Speed cable v2.0 HDMI-A male - HDMI-A male

Item : AK3905

Revision : 01-AA

Date : 13-07-2023

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.