



ITEM	PART	DESCRIPTION
A + B	Connector type	HDMI A male
	Contacts	Gold plated
	Hood	Molded plastic
	Shield type	Aluminum Mylar
	Conductor material	Copper
C	Cable colour	Black
	Outer jacket	PVC
	Wire gauge	28 AWG
	Outer diameter	Ø7.3 ±0.2mm
	Bend radius	40mm
	Temperature / humidity range	-20°C to +70°C (+5 %)
	Humidity range	45% to 65%
	Max bandwidth	48 Gb/s
	HDMI version	2.1
	HDMI standard	HDMI Ultra High Speed
	Max. resolution @ 60Hz	7680 x 4320 (8K)
	Max. resolution @ 120Hz	3840 x 2160 (4K)
	Max. resolution @ 144Hz	3840 x 2160 (4K)
D	Chroma sampling	4:4:4
	Colour bit depth	8 bits per colour
	Protective cap	PE

Item No.	Length(m)
AK3910	3.0m

ACT

Drawn by : EP

HDMI 8K Ultra High Speed cable v2.1

Item : AK3910

Revision : 01-AA

Date : 27-06-2024

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.