


ELECTRICAL TEST:

- 1.100% OPEN SHORT MIS WIRE TEST
- 2.CONTACT RESISTANCE: 3 OHM MAX
- 3.INSULATION RESISTANCE: 5M OHM MIN
- 4.HI-POT TEST: DC 300V/10ms
- 5.PASS 4K TEST

ITEM	PART	DESCRIPTION
A	Connector type	DisplayPort male 20P
	Contacts	Gold plated
	Locking	Snap-in
	Shell	Black ABS
B	Connector type	HDMI A male 19P
	Contacts	Gold plated
	Shell	Black ABS
	Shield type	Aluminum Mylar
	Conductor material	Copper
	Protective cap	Yes
C	Cable colour	Black
	Outer jacket	PVC
	Wire gauge	30 AWG
	Outer diameter	Ø5.5 ±0.2mm
	Bend radius	25 mm
	Temperature rating	-20°C to +70°C (+5%)
	Video signal	DisplayPort to HDMI
	Chipset	P8402A
	Version	DisplayPort 1.2 to HDMI High Speed with Ethernet
	Max. resolution @ 30Hz	3840 x 2160
	Max. resolution @ 60Hz	1920 x 1080
	Chroma sampling	4:4:4
	Color bit depth	8 bits per colour
	Power connected	no



NOTE: PIN 20 is only connected to power the PCBA and is not connected to the DP connector.

ACT

Drawn by : EP

Conversion cable DisplayPort male to HDMI-A male

Item : AK3991

Revision : 01-AB

Date : 24-12-2024

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.