


Specifications cable (A)	
Type	Patchcord - Duplex
Outer diameter	1.8mm
Tensile strength	90N (short time 150N)
Operation temp.	-20°C to +70°C
Outer Jacket	LSZH
Cable colour	Yellow
Cable printing	ACT Premium Single Mode Fiber Optical Patch Cable 9/125 OS2 LSZH
Specifications Connector (B,C)	
Connector	SC Duplex
Polishing Connector	UPC
Ferrule Connector	Ceramic Zirconia (ZrO2)
Ferrule Diamater	2.50mm
Housing	Blue (PBT)
Boot	Yellow/Blue (TPE)
Cap	Clear (PE)



ACT Single Mode Fiber Optic duplex patch cable 9/125 OS2

Item : RL39xx

Revision : 1.0

Date : 14-05-2024

Drawn by : YMN

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.

Specifications fiber	
Fiber type	Single Mode
Fiber class	OS2
Diameter core / cladding	9/125
Specifications optical performance	
Insertion Loss (IL) typical	0.1 dB
Insertion Loss (IL) maximum	0.2 dB
Return Loss (RL)	≥ 55 dB
Standard compliances	
ANSI/TIA-568-D	
ISO 11801 / IEC 60793-2	
Telcordia GR-326 CORE	
Fire performance	
Flame retardancy	IEC 60332-1-2
Smoke density LS	IEC 61034
Absence of halogen ZH	IEC 60754-1

Item	Length(m)
RL3900	0.50M
RL3901	1.00M
RL3951	1.50M
RL3902	2.00M
RL3903	3.00M
RL3905	5.00M
RL3907	7.00M
RL3910	10.0M
RL3915	15.0M
RL3920	20.0M
RL3930	30.0M
RL3950	50.0M



Drawn by : YMN

ACT Single Mode Fiber Optic duplex patch cable 9/125 OS2

Item : RL39xx

Revision : 1.0

Date : 14-05-2024

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.