



IEEE802.3at compliant PoE splitter for 12V products

Supplies power and 1GbE data simultaneously to devices not supporting PoE. Ideal for systems where access to power is limited by infrastructure layout.

1GbE Power over Ethernet Splitter 24W

IEEE802.3af/at

Compliant to IEEE802.3af/at which features a 1500V high voltage isolation PoE transformer and integrated high performance network filter

Safe and secure

Supports 44V–57V, auto-detects PSE power source with isolation circuit to help protect connected equipment from short circuit, over voltage, overcurrent and overheating.

1GbE support

10/100/1000Mb Ethernet and supports the full range of IEEE802.3 standards: IEEE 802.3 I, IEEE 802.3 u, IEEE 802.3 x, IEEE802.3af, IEEE802.3at.

Power Efficient

At 90% efficiency this PoE splitter is class leading and leads to its -20 to +50C operating temperature range.

Link Ports	
8p8c (RJ45)	1x
Cable Requirements	
CAT5e and above	100m / 328ft
Network Support	
Bandwidth	10/100/1000MbE
10/100 Support	Yes
Environmental	
Operating Temperature Range °C / °F	-20 to 50 °C / -4 to 122 °F
Storage Temperature °C / °F Range	-30 to 60 °C / -22 to 140 °F
Operating Humidity (%)	10% - 90% (non-condensing)
Storage Humidity (%)	5% - 95% (non-condensing)
Altitude m/ft	2,000 / 6562
Power Source	
12V 3-pin	1x
Input Power Supply	PoE (802.3.AF), PoE (802.3.AT)
Physical Design	
Construction Material	Robust plastic enclosure
U size	Zero
Width (mm) / (in.)	28 / 1.1
Height (mm) / (in.)	24 / 0.9
Depth (mm) / (in.)	81 / 3.2
Flying Lead Length (mm)	190
Weight (kg) / (lb)	0.1 / 0.2
Approvals and Standards	
Approvals	CE, FCC, ICES
Standards	ANSI 63.4, EN/IEC 62368-1, EN55032 /CISPR 32, EN55035/CISPR 35, EN61000-3-2, EN61000-3-3, FCC pt15B, IEE802.3at
Other	Cal Prop 65, China ROHS, EU REACH, UK REACH



1GbE Power over Ethernet Splitter 24W

What's in the Box?

1x 1GbE Power over Ethernet Splitter 24W

Ordering Information

PSU-POE-12VDC-2A

1GbE Power over Ethernet Splitter 24W

Adder and the Adder logo are trademarks of Adder Technology Ltd, Cambridge, UK. All other trademarks are the property of their respective owner and may be registered in the United States Patent and Trademark Office and in other countries. Information contained in this data sheet is up-to-date and correct as at the date of issue. As Adder Technology cannot control or anticipate the conditions under which this product may be used, each user should review the information in the specific context of planned use. Images are for illustrative purposes only. Adder reserves the right to make changes to this specification without notice.