

MOLDING:

DATE

REV.

REVISION

DRAFTING

CHECKED

2020/12/10

A/0

Initial

黃潤先

YE/GN

BLUE

BROWN

SF-04

②③

①

A

A

SF-82

③④⑤

①②③

BLUE

YE/GN

BROWN

WIRE MARKING(NO.129):

+ KEMA-KEUR

CE

S

N

D

FI

△

CEBEC 972

VD

NF-USE 1345

IEMMEQU H05VV-F 3G0.75MM² V-75 300/500V ORDINARY DUTY NSW17436 YFC BON-EAGLE

Jacket OD:6.8±0.5 mm

Insulation OD:2.4±0.2 mm

Conductor 0.75mm²x3G

A-A

Item

Color

Length (mm)

AK5145

Black

500±15

AK5146

Black

1000±20

AK5012

Black

1500±20

AK5015

Black

2000±30

Polarity and Conduction and Penetration Test

Dielectric Voltage Withstand Test : 2000V / 1 Sec

Electrical Performance (20°C)

Item

Parameter

Conductor Resistance

≤ 26.0Ω/1000m

Voltage Rating

AC 300V/500V

⑤

Housing

IEC C13 three Pin(SF-82)inner frame , Black

1PC

④

Terminal

IEC C13 ,Female terminal,matching 20-16AWG wire

3PCS

③

Molding

Black 40P PVC

A/R

②

Terminal

European standard,black french connector SF-04.

1PC

①

CABLE

H05VV-F 3G 0.75mm² Black PVC

A/R

No.

TITLE

DESCRIPTION

Q'TY

Unless specified on the drawing, tolerances are per the follows:

X.

±0.20

X°

±3

.X

±0.10

.X°

±0.3

.XX

±0.05

ACT

DRAW. NO

YFAC-S200065

CUSTOMER

CUST' R P/N

SCALE

NONE

UNIT

mm

TITLE

H05VV-F 3G 0.75mm² SF-04 TO SF-82 Black CABLE ASS'Y

DRAW

CHECK

APPROVED

DATE

2020.12.10

DATE

SHEET

1 of 1

Cable Spec NO.

/

Part Number

--

Note

RoHS2.0

Reach

GP

HF

Other