

## SDI to Analog



STA-500

## Introduction

It is superior to convert from SDI to Analog video out.

## Feature

- Input : HD/SD-SDI inputs
- Output: Component, Composite and HD/SD-SDI
- Stereo L/R Audio output, AES EBU output
- SDI loop through output

## Competitiveness

- Compact size and light weight
- Simply easy to use
- Fully compatible with all your SD and HD devices.

## Specification

### Video Input

|               |                                                                      |
|---------------|----------------------------------------------------------------------|
| Digital Input | HD/SD-SDI<br>480i(29.9/30), 576i(25)                                 |
| Resolutions   | 720p(50/59.94/60), 1080i(25/29.97/30)<br>1080p(23.98/24/25/29.97/30) |
| Impedance     | 75Ω                                                                  |
| Aspect Ratio  | 4:3, 16:9                                                            |

### Audio Input

|               |                     |
|---------------|---------------------|
| Digital Input | HD/SD-SDI(Embedded) |
| Sampling Rate | 48KHz               |
| Connector     | BNC (75Ω)           |

### Video Output

|                |                                                                      |
|----------------|----------------------------------------------------------------------|
| Digital Output | HD/SD-SDI(Loop Through)                                              |
| Analog Output  | Composite, Component<br>480i(29.9/30), 576i(25)                      |
| Resolutions    | 720p(50/59.94/60), 1080i(25/29.97/30)<br>1080p(23.98/24/25/29.97/30) |
| Output level   | 1.0 Vpp                                                              |
| Aspect Ratio   | 4:3, 16:9                                                            |

### Audio Output

|                 |                   |
|-----------------|-------------------|
| Digital Output  | AESEBU            |
| Sampling Rate   | 48KHz             |
| Analog Output   | Analog Audio      |
| Frequency Range | 20Hz~20KHz        |
| Impedance       | 600Ω              |
| Connector       | 6.35mm Phone Jack |

### General

|                    |              |
|--------------------|--------------|
| Power Requirements | DC 12V 1A    |
| Weight             | 0.22Kg       |
| Dimensions         | 110x90x28 mm |

## Head Office / Laboratory

#40-12 Teheran-ro 38-gil, Gangnam-gu, Seoul, Korea 135-920  
 Phone : +82 2 6005 9118  
 Fax : +82 2 3453 8338  
 E-mail : castwin@castwin.com

[www.castwin.com](http://www.castwin.com)