



D-SUB HIGH DENSITY

Solder pin – Straight – Precision machined contacts



RoHS compliant – CSA listed, File No.: LR 115000-1 – UL listed, File No.: E202784

SOCKET CONNECTOR



No. of pos.	A -0.76	B -0.25	C
15	31.19	16.46	25.00 +0.12
26	39.52	24.79	33.30 +0.15
44	53.42	38.50	47.04 +0.13
62	69.70	54.96	63.50 +0.13
78	67.31	52.55	61.10 +0.14

PCB layout: Kat1iT9A

DESCRIPTION


■ Mounting styles:

- with through-hole, Ø .118" / 3 mm
- with 4-40 UNC or M3 threaded insert
- with 4-40 UNC front / M3 threaded rear spacer
- with M3 front / 4-40 UNC or M3 threaded rear spacer with PCB clip
- with 4-40 UNC or M3 front and threaded rear spacer with PCB clip

■ Quality class 3 (also available in quality class 1)



■ Shell: Steel tin plated (brass tin plated or stainless steel available on request)

PLUG CONNECTOR





No. of pos.	A -0.76	B -0.25	C	D -0.3
15	31.19	16.79	25.00 +0.12	6.12
26	39.52	25.12	33.30 +0.15	6.12
44	53.42	38.84	47.04 +0.13	5.99
62	69.70	55.30	63.50 +0.13	5.99
78	67.31	52.68	61.10 +0.14	5.99

PCB layout: Kat1iU0A




78 pos. = Dim. in (_)



78 pos. = Dim. in (_)

ORDER DATA




SOCKET CONNECTOR

No. of pos.	Mounting style	Part Number
15	Through-hole	164 A 17159 X
26	Through-hole	164 A 17169 X
44	Through-hole	164 A 17179 X
62	Through-hole	164 A 17189 X
78	Through-hole	164 A 17199 X

PLUG CONNECTOR

No. of pos.	Mounting style	Part Number
15	Through-hole	163 A 16749 X
26	Through-hole	163 A 16759 X
44	Through-hole	163 A 16769 X
62	Through-hole	163 A 16779 X
78	Through-hole	163 A 16789 X



SOCKET CONNECTOR

No. of pos.	Mounting style	Part Number
15	4-40 UNC Threaded insert	164 A 17209 X
26	4-40 UNC Threaded insert	164 A 17219 X
44	4-40 UNC Threaded insert	164 A 17229 X
62	4-40 UNC Threaded insert	164 A 17239 X
78	4-40 UNC Threaded insert	164 A 17249 X
15	M3 Threaded insert	164 A 17259 X
26	M3 Threaded insert	164 A 17269 X
44	M3 Threaded insert	164 A 17279 X
62	M3 Threaded insert	164 A 17289 X
78	M3 Threaded insert	164 A 17299 X


PLUG CONNECTOR

No. of pos.	Mounting style	Part Number
15	4-40 UNC Threaded insert	163 A 16799 X
26	4-40 UNC Threaded insert	163 A 16809 X
44	4-40 UNC Threaded insert	163 A 16819 X
62	4-40 UNC Threaded insert	163 A 16829 X
78	4-40 UNC Threaded insert	163 A 16839 X
15	M3 Threaded insert	163 A 16849 X
26	M3 Threaded insert	163 A 16859 X
44	M3 Threaded insert	163 A 16869 X
62	M3 Threaded insert	163 A 16879 X
78	M3 Threaded insert	163 A 16889 X

D-SUB HIGH DENSITY – MOUNTING STYLES


Solder pin – Straight – Precision machined contacts

ORDER DATA



SOCKET CONNECTOR		
No. of pos.	Mounting style	Part Number
15	4-40 UNC Front / M3 Threaded rear spacer	164 A 17309 X
26	4-40 UNC Front / M3 Threaded rear spacer	164 A 17319 X
44	4-40 UNC Front / M3 Threaded rear spacer	164 A 17329 X
62	4-40 UNC Front / M3 Threaded rear spacer	164 A 17339 X
78	4-40 UNC Front / M3 Threaded rear spacer	164 A 17349 X


PLUG CONNECTOR		
No. of pos.	Mounting style	Part Number
15	4-40 UNC Front / M3 Threaded rear spacer	163 A 16899 X
26	4-40 UNC Front / M3 Threaded rear spacer	163 A 16909 X
44	4-40 UNC Front / M3 Threaded rear spacer	163 A 16919 X
62	4-40 UNC Front / M3 Threaded rear spacer	163 A 16929 X
78	4-40 UNC Front / M3 Threaded rear spacer	163 A 16939 X



SOCKET CONNECTOR		
No. of pos.	Mounting style	Part Number
15	4-40 UNC Threaded rear spacer PCB clip	164 A 17359 X
26	4-40 UNC Threaded rear spacer PCB clip	164 A 17369 X
44	4-40 UNC Threaded rear spacer PCB clip	164 A 17379 X
62	4-40 UNC Threaded rear spacer PCB clip	164 A 17389 X
78	4-40 UNC Threaded rear spacer PCB clip	164 A 17399 X
15	M3 Threaded rear spacer PCB clip	164 A 17409 X
26	M3 Threaded rear spacer PCB clip	164 A 17419 X
44	M3 Threaded rear spacer PCB clip	164 A 17429 X
62	M3 Threaded rear spacer PCB clip	164 A 17439 X
78	M3 Threaded rear spacer PCB clip	164 A 17449 X

PLUG CONNECTOR		
No. of pos.	Mounting style	Part Number
15	4-40 UNC Threaded rear spacer PCB clip	163 A 16949 X
26	4-40 UNC Threaded rear spacer PCB clip	163 A 16959 X
44	4-40 UNC Threaded rear spacer PCB clip	163 A 16969 X
62	4-40 UNC Threaded rear spacer PCB clip	163 A 16979 X
78	4-40 UNC Threaded rear spacer PCB clip	163 A 16989 X
15	M3 Threaded rear spacer PCB clip	163 A 16999 X
26	M3 Threaded rear spacer PCB clip	163 A 17009 X
44	M3 Threaded rear spacer PCB clip	163 A 17019 X
62	M3 Threaded rear spacer PCB clip	163 A 17029 X
78	M3 Threaded rear spacer PCB clip	163 A 17039 X

PCB clip .122" / 3.1 ± .004" / 0.10 mm hole diameter and .063" / 1.6 mm circuit board thickness



SOCKET CONNECTOR		
No. of pos.	Mounting style	Part Number
15	4-40 UNC Front / Threaded rear spacer PCB clip	164 A 17459 X
26	4-40 UNC Front / Threaded rear spacer PCB clip	164 A 17469 X
44	4-40 UNC Front / Threaded rear spacer PCB clip	164 A 17479 X
62	4-40 UNC Front / Threaded rear spacer PCB clip	164 A 17489 X
78	4-40 UNC Front / Threaded rear spacer PCB clip	164 A 17499 X
15	M3 Front / Threaded rear spacer PCB clip	164 A 17509 X
26	M3 Front / Threaded rear spacer PCB clip	164 A 17519 X
44	M3 Front / Threaded rear spacer PCB clip	164 A 17529 X
62	M3 Front / Threaded rear spacer PCB clip	164 A 17539 X
78	M3 Front / Threaded rear spacer PCB clip	164 A 17549 X

PLUG CONNECTOR		
No. of pos.	Mounting style	Part Number
15	4-40 UNC Front / Threaded rear spacer PCB clip	163 A 17049 X
26	4-40 UNC Front / Threaded rear spacer PCB clip	163 A 17059 X
44	4-40 UNC Front / Threaded rear spacer PCB clip	163 A 17069 X
62	4-40 UNC Front / Threaded rear spacer PCB clip	163 A 17079 X
78	4-40 UNC Front / Threaded rear spacer PCB clip	163 A 17089 X
15	M3 Front / Threaded rear spacer PCB clip	163 A 17099 X
26	M3 Front / Threaded rear spacer PCB clip	163 A 17109 X
44	M3 Front / Threaded rear spacer PCB clip	163 A 17119 X
62	M3 Front / Threaded rear spacer PCB clip	163 A 17129 X
78	M3 Front / Threaded rear spacer PCB clip	163 A 17139 X

PCB clip .122" / 3.1 ± .004" / 0.10 mm hole diameter and .063" / 1.6 mm circuit board thickness

PCB layout: Kat1i79A

PCB layout: Kat1iU0A