

OPF-H1000D


HDMI Fiber Optic Extender



The IDK OPF-1000D Fiber Optic Extender is an extender for the long haul transmission of HDCP-compliant HDMI video and unidirectional RS-232 control signals over fiber optic cabling. It also supports daisy chaining. Input signals are extended without compression. Audio can be de-embedded from the HDMI signal and output as analog audio at the transmitter side.

FRONT & REAR PANEL

■ Front & Rear Panel




- Specifications can be changed without prior notice.
- An attached power cord is used only for this product. Please do not use it for other uses.
- „HDMI“, logotype of „HDMI“ and „High-Definition Multimedia Interface“ are trademarks or registered trademarks of HDMI Licensing LLC or registered trademarks in the U.S.A and other countries.
- „PLink“ is a trademark registration or an application for trademark registration in JAPAN, the United States, and other countries and regions.
- JBMA: Japan Business Machine and Information System Industries Association.

PRODUCT SELECTION

Parts Number	Fiber Type	Max. Distance	Order No.
OPF-TH1000D-MM	Multimode	985ft (approx.) <300m> *OM3 fiber	8673-0019-01
OPF-RH1000D-MM			8673-0020-01
OPF-TH1000D-SM	Singlemode	2.92 miles (approx.) <4,7km> *OS1 fiber	8673-0021-01
OPF-RH1000D-SM			8673-0022-01

CONNECTION EXAMPLE



SFP

Item	Multimode fiber	Singlemode fiber
Connector	2 LC connectors (Duplex)	
Wave length	850 nm (Oxide VCSEL Laser (*8))	1310 nm (Fabry-Perot laser (*8))
Max. extensions distance	OM3: 985ft(approx.)<300m>OM4: 3.280ft(<1km>	OS1:2.92 miles (approx.) <4,7km>
Optical power level	Input	Over -13 dBm
	Output	-9dBm to -2,5 dBm
		-8,4dBm to -3dBm

Item				Description		
Model number				OPF-TH1000D(Transmitter)	OPF-RH1000D(Receiver)	
Input	Video	Number/Signal		1 input / HDMI (*1)- HDCP: Pass through- CEC: Pass through- TMDS Single Link- TMDS clock: 25 MHz to 165 MHz	1 input / Optical signal for extension	
		Connector		1 female HDMI Type a(*2)	1 LC connector	
		Others		Color depth: 24bit		
		Formats		VESA: VGA/SVGA/XGA/WXGA (1280x768) /WXGA(1280x800)/Quad-VGA/SXGA/WXGA(1360x768)/WXGA(1366x768)/SXGA+/WXGA+/WXGA+ +/UXGA/WSXGA+/WUXGA* WUXGA only supports Reduced BlankingSDTV/HDTV: 480i/480p/576i/576p/720p/1080i/1080p		
	Audio	Digital	Digital Number/Signal	1 input / Multi-channel linear PCMup to 8 channels- Sampling frequency: 32 kHz to 192 kHz- Sample size: 16 bit to 24 bit-Reference level:-20 dBFS- Max. input level: 0 dBFS	1 input / Optical signal for extension	
			Connector	1 female HDMI Type A (*2)	1 LC connector	
		Analog (*4)	Number/Signal	output / Optical signal for extension	1 output / HDMI (*1)- HDCP: Pass through- CEC: Pass through- TMDS Single Link- TMDS clock: 25 MHz to 165 MHz	
			Connector	1 stereo mini jack (3.5 mm)	1 LC connector	
Output	Video	Digital	Number/Signal	1 output / Optical signal for extension	1 output / Multi-channel linear PCMup to 8 channels- Sampling frequency: 32 kHz to 192 kHz- Sample size: 16 bit to 24 bit-Reference level:-20 dBFS- Max. input level: 0 dBFS	
			Connector	1 LC connector	1 female HDMI Type A (*2)	
		Daisy Chain	Number/Signal		1 output / Optical signal for extension	
			Connector		1 LC connector	
		Others	Others	color depth: 24 bit (*3)		
		Formats		VESA: VGA/SVGA/XGA/WXGA (1280x768) /WXGA (1280x800)/Quad-VGA/SXGA/WXGA(1360x768)/WXGA(1366x768)/SXGA+/WXGA+/WXGA+ +/UXGA/WSXGA+/WUXGA* WUXGA only supports output as Reduced BlankingSDTV/HDTV: 480i/480p/576i/576p/720p/1080i/1080p		
		Audio	Digital	Number/Signal	1 output / Optical signal for extension	1 output / Multi-channel linear PCMup to 8 channels- Sampling frequency: 32 kHz to 192 kHz- Sample size: 16 bit to 24 bit-Reference level:-20 dBFS- Max. input level: 0 dBFS
	Connector			1 LC connector	1 female HDMI Type A (*2)	
	Daisy Chain		Number/Signal	-	1 output / Optical signal for extension	
			Connector	-	1 LC connector	
	Analog (*5)		Number / Signal	1 output / Optical signal for extension	1 output / Stereo LR unbalanced signal- Output impedance: 75 Ω- Reference level: -10 dBu,- Max. output level: +10 dBu	
			Connector	1 LC connector	1 stereo mini jack (3.5 mm)	
	Plug & Play				DDC2B (Built in EDID) *Max resolution selectable using built in EDID	
		Suitable cable		Simplex fiber cable, SFP module (2LC connectors)		
	Fiber optic cable	Polishing (*6)		SFP for Multimode: PC (recommended)SFP for Singlemode: UPC (recommended), SPC supported * APC is not supported		
	Signal transmission distance (*7)				Multimode fiber (OM3): 985ft (approx.) <300m>Multimode fiber (OM4): 3,280ft (approx.) <1km>Singlemode fiber (OS1): 2.92 miles (approx.) <4.7km>	
	Control	Serial control port	Number / Signal	1 port / simplex up to 115.2 kbps		
			Connector	1 male 9-pin D-Sub		
	AC adapter	Input: 100 - 240 VAC ± 10%, 50 Hz/60 Hz ± 3 HzOutput: DC 5V 3A (AC adapter supplied)				
	Power consumption	Around 9 Watts				
	Dimensions	7.87(W)x1.18(H)x4.17(D) “(approx.)<200(W)x30(H)x106(D)mm>(Quarter rack, not including projections)				
	Weight	0.88 lbs. (approx.)<0.6kg>				
	Temperature	Operating temperature: 32°F ~ 104°F<0°C ~ +40°C>Storage temperature: -4°F ~ +176°F<-20°C ~ +80°C>				
Others	Humidity	Operating Storage humidity: 20% ~ 90% (Non Condensing)				