

SCALE 1/10





Specification	
1. Panel Cover	SECC, 1.2mm thickness, BK
2. Rack mount brackets	SPCC, 2.0mm thickness, BK
3. Grommet	10 pcs, PVC, BK
4. Tray	SECC 1.2mm thickness, BK
5. Removable L-pin	2pcs. SPCC, Ø5.0*40mm
6. Cable routing spool	2 sets, ABS, IV
7. 24-port splice tray	1 pc, ABS+PC, BK
8. Front plate	SPCC, 1 .2mm thickness, BK
Dimensions	Width 19" (482.6mm) x Depth 10" (255.0mm) x Height 1U (44.0mm)
Shelf mounting adjustment range	0~40 mm

Adapter (9)	
SC duplex flange adapter	24pcs loaded
	Housing: PC+10 % GF, UL94V-0, BL
	Sleeve: Zirconia sleeve
Durabiliy	500 cycles.
Tensile Strength	4.5kgf.
Insertion Loss	< 0.2 dB.
Operating Temperature	-20°C to +70°C
Storage Temperature	-40°C to +80°C

Accessory	
Cable tie	5pcs, 150mm Length, BK, Nylon66
Cable twist tie	5pcs
Cable gland	2pcs, M20
24-port splice tray	1 pc, ABS+PC, BK

FIBER PANEL 24X DUPLEX SC OS2

Item : FA2038

Revision : 1.0

Date : 28-06-2024

Drawn by : DANIEL

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.

0 10cm