

Customer Name										DATE	REV.	REVISION	DRAFTING	CHECKED							
Customer Part No.										2013. 01. 03	A/0	New	DHY	ZCY							
										2021. 07. 09	A/1	Add PoE Rating	XHJ	ZCY							
										2022. 09. 13	A/2	Add datasheet	CZ	ZCY							
										2024. 12. 09	A/3	Add datasheet	CZ	ZCY							
Length																					
Marking(FP1817): CE UKCA 17 ACT Cat6a S/FTP 4X2XAWG26/7 CU PVC ANSI/TIA-568.2-D ISO/IEC 11801 CLASS EA EN 50288-10-2/IEC 60332-1-2 ▲ 26AWGX4P TYPE CMX(UL) E477294-01 XXXXXM																					
305M/R W x H(380mm X 238mm)																					
CROSS-SECTION OF CABLE																					
Conductor		Bare Copper 26AWG																			
Insulation		Thickness:Min at any point:0.20mm Max Avg:0.35mm Diameter:1.05±0.08mm																			
	PVC	Thickness:Min at any point:0.50mm Max Avg:0.60mm Diameter:5.8±0.3mm																			
JacketWire		Cat.6A S/FTP STR 26AWGx4P																			
Length		305±1.5M																			
Color=YY		Gray (RAL7045)																			
Note: 1.Minimum bending radius: 8xOD (Outer diameter) 2.Operating(Storage) temperature: -20℃ ~ +60℃,Humidity: <60%RH. 3.Maximum PoE rated 60W (Reference) 4.WOODEN DRUM SIZE: W x H(380mm X 238mm)																					
Material		Part Number		Note		RoHS Reach GP HF Other				DRAW. NO		FP700B		TITLE		Cat. 6A S/FTP STR 26AWGx4P					
										CUSTOMER		/		DRAW		CZ		DATE		2024. 12. 09	
										CUST' R P/N		/		CHECK		加蓋章 2024.12.30 繪成第		DATE		2024. 12. 09	
										UNIT		mm		APPROVED		加蓋章 2024.12.30 陳城		SHEET			

