

Soldering Irons and Tips

Butane Gas Powered Soldering Irons

Weller®



Order No.	Model	Description	
005 16 059 99	Pyropen Piezo	Pyropen Butane gas powered profi line soldering iron	WL 1010

- Self ignition (Piezo)
- One filling lasts ~3 hours
- Temperature range soldering: 350°C–500°C, hot air: ~650°C
- Metal box with iron holder, cleaning sponge and burn proof accessory pocket

consists of:

005 16 121 99	70-01-02	Soldering iron Chisel tip 3,0 mm
005 16 142 99	70-01-52	Hot air nozzle Ø 4,9 mm
005 16 159 99	70-01-55	Reflector Ø 6,0 mm, 18,0 mm width for heat shrinking
005 16 160 99	RB-TS	Butane gas refill canister 0,75 ml
005 16 156 99	7040U	Metall box
005 16 281 99	7042	Burn proof accessory pocket Iron holder Cleaning sponge

Soldering Tips for Pyropen and Pyropen Piezo

	Order No.	Model	Description	Width A	
	005 16 120 99	70-01-01	Needle	Ø 1,0 mm	1202
	005 16 124 99	70-01-05	Needle slim	Ø 0,5 mm	
	005 16 129 99	70-01-10	Needle bent 30°	Ø 1,0 mm	1296

Soldering Tips for Pyropen and Pyropen Piezo

	Order No.	Model	Description	Width A	Thickness B
	005 16 121 99	70-01-02	Chisel	3,0 mm	1210
	005 16 132 99	70-01-13	Chisel	5,0 mm	
	005 16 130 99	70-01-11	Chisel	7,7 mm	
	005 16 122 99	70-01-03	Round spade	Ø 2,0 mm	
	005 16 123 99	70-01-04	Round spade	Ø 3,0 mm	
	005 16 125 99	70-01-06	Spade conical	Ø 2,0 mm	
	005 16 127 99	70-01-08	Round spade 35°	Ø 2,0 mm	
	005 16 140 99	70-01-50	Hot air nozzle	Ø 1,7 mm	
	005 16 141 99	70-01-51	Hot air nozzle	Ø 3,3 mm	
	005 16 142 99	70-01-52	Hot air nozzle	Ø 4,9 mm	
	005 16 143 99	70-01-53	Hot air nozzle	Ø 7,0 mm	
	005 16 151 99	70-07TU	Torch ejector		
	005 16 150 99	70-07SU	Solder ejector		
	005 16 159 99	70-01-55	Reflector for heat shrinking	Ø 6,0 mm	18,0 mm
	005 16 158 99	70-01-54	Reflector for heat shrinking	Ø 8,0 mm	22,0 mm