

1		2		3		4		5		6		7		8			
								REV.		ECN NO.		DATE		SIGN		DESCRIPTION	
								B		C201735		2020/11/09		Ruru		B X6	
								C		C210226		2021/03/30		Vicky		C X4	

</



Note:

- * RoHS Compliant
- * Important dimension
- * Waterproof rate: IPX8, mated 1m/24h
IPX9K, mated
- * Connector
 - Housing: Thermoplastic, Black
 - Pin: Copper alloy, Gold plated
 - O-Ring: Rubber, Green
 - Nut: Metal
 - Outer Mold: Thermoplastic, Black
- * Cable: UL20549, PUR Jacket, Black
- * Cable Length Tolerance: 0.5M < L ≤ 1M: +60/-0 mm
1M < L ≤ 3M: +120/-0 mm
3M < L ≤ 5M: +160/-0 mm
5M < L ≤ 10M: ±100 mm
10M < L ≤ 20M: ±200 mm
20M < L ≤ 30M: ±300 mm
30M < L ≤ 99M: ±500 mm

UNIT:mm
TOLERANCE
±0.5mm

TITLE
ACC, SEN, A Code, DB-ENDED
FF
SCALE
1:2
SIZE
A4
SHEET
1 OF 2
REV.
C
WC-REV.
QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO
DWG NO
CUSTOMER
ALTW

DRAWN BY
Ruru
CHECKED BY
Rita
APPROVED BY
Max

DATE
2018-12-05
DATE
2018-12-05
DATE
2018-12-05

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

A