



#### General (A)

Type	PDU 19" CEE7/7 - Type F (9x)
Formfactor	19" 1U
Maximum load	4000W (250 V 50-60Hz / 16 A)
Colour	Shell=Black ; Sockets=Black
Temperature / humidity range	Operational -5° to +60° / 5%-95% Non condensing Storage -15° to +65° / 5%-95% Non condensing
Brackets	2 metal brackets, hor/vert multiple positioning
Accessories	2x Nut / 2x Bolt / 2x Washer
Packaging	Cardboard box

#### Cable (B)

Standardized cable type	H05VV-F3G 1.5
Conductor material	Bare Copper
Wire gauge	1.5 mm <sup>2</sup>
Cable colour	Black

#### Plug (C,D)

Connector C	CEE7/7
Connector D	Type F 9 sockets

**ACT**

Drawn by : EL

Extension lead PDU 19" CEE7/7 with 9 type F sockets, 3m

Item : PD3002

Date : 25-11-2024

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only.  
This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions.  
Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.