

General (A)	
Type	PDU 19'' C14 - Type F (8x) - 10A Overload
Formfactor	19" 1U
Maximum load	2500W (250V 50-60Hz / 10A)
Colour	Shell=Silver ; Sockets=Red
Protection	10A Overload, resettable
Temperature / humidity range	Operational -5° to +60° / 5%-95% Non condensing
	Storage -15° to +65° / 5%-95% Non condensing
Brackets	2 metal brackets, hor/vert multiple positioning
Accessories	2x Nut / 2x Bolt / 2x Washer
Packaging	Cardboard box

Cable (B)	
Standarized cable type	H05VV-F3G 1.0
Conductor material	Bare Copper
Wire gauge	1.0 mm²
Cable colour	Black

Plug (C,D)	
Connector C	C14
Connector D	Type F 8 sockets

Drawn by : EL

Extension lead PDU 19'' C14 - Type F (8x) 10A overload protection, 3m

Item : PD3004

Date : 25-11-2024

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.