



General (A)	
Type	PDU 19" CEE7/7 - Type F (8x) -Switch
Formfactor	19" 1U
Maximum load	4000W (250V 50-60Hz / 16A)
Colour	Shell=Black ; Sockets=Black
Switch	Illuminated switch with protection cap
Temperature / humidity range	Operational -5° to +60° / 5%-95% Non condensing
	Storage -15° to +65° / 5%-95% Non condensing
Brackets	2 metal brackets, hor/vert multiple positioning
Accessories	2x Nut / 2x Bolt / 2x Washer
Packaging	Cardboard box
Cable (B)	
Standardized cable type	H05VV-F3G 1.5
Conductor material	Bare Copper
Wire gauge	1.5 mm ²
Cable colour	Black
Plug (C,D)	
Connector C	CEE7/7
Connector D	Type F 8 sockets



Drawn by : EL

Extension lead PDU 19" CEE7/7 with 8 type F sockets, 2.5m

Item : PD3005

Date : 25-11-2024

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only.
This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions.
Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.