




#: Matching DIM. *: Important DIM. Others General DIM.	DRAWING	13.MAY.2022	YSL	ACT		
	CHECK	13.MAY.2022	DAY			
	APPROVAL	13.MAY.2022	FRANK			
GENERAL TOLERANCE OF DIMENSIONS X.XXX ±0.1 X.XX ±0.2 X.X ±0.3	SCALE	1/1 (A4)	UNIT	mm	ITEM NO.:	
	DRAWING NO.		Indoor&Outdoor Cable 4C OM4 4xLC to 4xLC 900um buffer(S01)		DES.: Indoor&Outdoor Cable 4C OM4 4xLC to 4xLC 900um buffer	
	DRAWING CLASSIFICATION		S	SHEET	1 OF 3	01

Specification:

1. LC Connector :

Mode	Ferrule	Housing	Boot	Cap
MM Low Loss	Zirconia(Ø1.25mm)	Ivory(PC)	White(TPV)	White(PE)

2. Cable Type:

- 2-1. 4C Ø6.5mm Indoor/Outdoor Cable with 900um Tight Buffer, UV Resistance.
2-2. Ø0.9mm Jacket for 4 Colors.

Category	Jacket O.D.	Jacket Material	Color
OM4(50/125um)	Ø6.5mm	LSZH	Black

3. Heat Shrink Tubing Length : 60mm


4. Length : x Meter

5. Protective Tube : Transparent, 12x15mm, PVC Material.

6. Heat Shrink Tubing Length : 60mm

Performance:

- a. Insertion Loss : Typical 0.1dB, Max. < 0.15dB
b. Return Loss : >35 dB
c. Insertion Loss will be Increased after 500 mating: 0.2 dB Max
d. Operating Temperature: -20°C to +70°C
e. Storage Temperature: -40°C to +80°C



Cable Section (SCALE 5/1)

"#": Matching DIM. "*": Important DIM. Others General DIM. GENERAL TOLERANCE OF DIMENSIONS X.XXX ±0.1 X.XX ±0.2 X.X ±0.3	DRAWING	13.MAY.2022	YSL		
	CHECK	13.MAY.2022	DAY		
	APPROVAL	13.MAY.2022	FRANK		
		DATE	NAME	ITEM NO.:	
	SCALE	1/1 (A4)	UNIT	mm	DES.: Indoor&Outdoor Cable 4C OM4 4xLC to 4xLC 900um buffer
			DRAWING NO.	Indoor&Outdoor Cable 4C OM4 4xLC to 4xLC 900um buffer(S01)	
	DRAWING CLASSIFICATION		S	SHEET	2 OF 3
					01

Standard compliance:

- IEC 61754-20 Fibre optic connector interfaces – Type LC connector family
- IEC 61300-3-47 Examinations and measurements – End face geometry of PC/APC spherically polished ferrules using interferometry
- IEC 60794-2-20 Indoor cables – Family specification for multi-fibre optical cables
- IEC 60794-1-2 Basic optical cable test procedures
- IEC 60332-1-2 Test for vertical flame propagation for a single insulated wire or cable
- IEC 60754-1 Determination of the halogen acid gas content
- IEC 60754-2 Determination of acidity (by pH measurement) and conductivity
- IEC 61034-2 Measurement of smoke density of cables burning under defined conditions

Cable Pulling Tensile Force Max. 350N.


Acc’y: 2 pieces M20 cable gland, fits cable o.d. 8-14mm

Package:

Bag pack when cable length <120M

Reel pack when cable length >=120M, ref. below table.

4C	Reel Weight	Reel Dimension
120M	1.7KG	H327mm x ϕ 345mm
121-240M	2KG	H327mm x ϕ 400mm
241-290M	2.8KG	H330mm x ϕ 450mm
291M up	3KG	H330mm x ϕ 480mm

"#" : Matching DIM. "*" : Important DIM. Others General DIM. GENERAL TOLERANCE OF DIMENSIONS X.XXX ±0.1 X.XX ±0.2 X.X ±0.3	DRAWING	13.MAY.2022	YSL		
	CHECK	13.MAY.2022	DAY		
	APPROVAL	13.MAY.2022	FRANK		
		DATE	NAME	ITEM NO.:	
	SCALE	1/1 (A4)	UNIT	mm	DES.: Indoor&Outdoor Cable 4C OM4 4xLC to 4xLC 900um buffer
		DRAWING NO.	Indoor&Outdoor Cable 4C OM4 4xLC to 4xLC 900um buffer(S01)		
	DRAWING CLASSIFICATION	S	SHEET	3 OF 3	