

1

2

3

4

5

6

A

A

B

B

C

C

D

D

Specifications Installation cable (A)	
Type	Indoor/Outdoor cable
Outer diameter	6.5mm
Tensile strength	350N
Operation temp.	-20°C to +70°C
Storage temp.	-40°C to +80°C
Outer Jacket	LSZH
Euro fire class	B2ca s1, d1, a1
Cable colour	Black
UV resistance	Yes
Cable printing	CE MM/YY ACT 24F 9/125 OS2 10280010 xxxxM DoP: 1320-2231 B2ca, s1, d1, a1 NB0598 Communications supply in-/outdoor (MM=month, YY=year)
Specifications Heat Shrink Tubing (B,C)	
Length	80mm
Specifications Fanout cable (D,E)	
Type	Tubing
Outer diameter	0.9mm
Operation temp.	-20°C to +70°C
Storage temp.	-40°C to +80°C
Colors	Blue, Orange, Green, Brown, Gray, White, Red, Black, Yellow, Purple, Pink, Aqua
Cable marking	1 to 24
Fanout length	500mm (+50mm-0mm) - 940mm (+50mm-0mm)
Fanout staggered increments	40mm
Specifications Connector (F,G)	
Connector	LC
Polishing Connector	UPC
Ferrule Connector	Ceramic Zirconia (ZrO2)
Ferrule Diameter	1.25mm
Housing	Blue (PC)
Boot	White (TPV)
Cap	White (PE)



ACT Single Mode Fiber Optic Indoor / Outdoor cable 9/125 OS2

Item : RL44xx-B2ca

Revision : 1.0

Date : 04-07-2024

Drawn by : YMN

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.

1

2

0


3

4


10cm

5

6



Specifications fiber	
Fiber type	Single Mode
Fiber class	OS2
Diameter core / cladding	9/125
Specifications optical performance	
Insertion Loss (IL) typical	0.1 dB
Insertion Loss (IL) maximum	0.15 dB
Return Loss (RL)	≥ 55 dB
Standard compliances	
IEC 61754-20	Fibre optic connector interfaces - Type LC connector family
IEC 61300-3-47	Examinations and measurements - End face geometry of PC/APC spherically polished ferrules using interferometry
IEC 60794-2-20	Indoor cables - Family specification for multi-fibre optical cables
IEC 60794-1-2	Basic optical cable test procedures
IEC 60332-1-2	Test for vertical flame propagation for a single insulated wire or cable
IEC 60754-1	Determination of the halogen acid gas content
IEC 60754-2	Determination of acidity (by pH measurement) and conductivity
IEC 61034-2	Measurement of smoke density of cables burning under defined conditions

	ACT Single Mode Fiber Optic Indoor / Outdoor cable 9/125 OS2	
	Item : RL44xx-B2ca	Revision : 1.0
	Date : 04-07-2024	
Drawn by : YMN	<small>This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.</small>	

