





	8	7	6	5	4	3	2	1																															
H	<table><tr><th colspan="2">Specifications Installation cable (A)</th></tr><tr><td>Type</td><td>Indoor/Outdoor cable</td></tr><tr><td>Outer diameter</td><td>6.5mm</td></tr><tr><td>Tensile strength</td><td>350N</td></tr><tr><td>Operation temp.</td><td>-20°C to +70°C</td></tr><tr><td>Storage temp.</td><td>-40°C to +85°C</td></tr><tr><td>Outer Jacket</td><td>LSZH</td></tr><tr><td>Cable colour</td><td>Black</td></tr><tr><td>UV resistance</td><td>Yes</td></tr><tr><td>Cable printing</td><td>CE MM/YY ACT 24F 9/125 OS2 10280010 xxxxM DoP: 1320-2231 B2ca, s1, d1, a1 NB0598 Communications supply in-/outdoor (MM=month, YY=year)</td></tr></table>								Specifications Installation cable (A)		Type	Indoor/Outdoor cable	Outer diameter	6.5mm	Tensile strength	350N	Operation temp.	-20°C to +70°C	Storage temp.	-40°C to +85°C	Outer Jacket	LSZH	Cable colour	Black	UV resistance	Yes	Cable printing	CE MM/YY ACT 24F 9/125 OS2 10280010 xxxxM DoP: 1320-2231 B2ca, s1, d1, a1 NB0598 Communications supply in-/outdoor (MM=month, YY=year)	H										
Specifications Installation cable (A)																																							
Type	Indoor/Outdoor cable																																						
Outer diameter	6.5mm																																						
Tensile strength	350N																																						
Operation temp.	-20°C to +70°C																																						
Storage temp.	-40°C to +85°C																																						
Outer Jacket	LSZH																																						
Cable colour	Black																																						
UV resistance	Yes																																						
Cable printing	CE MM/YY ACT 24F 9/125 OS2 10280010 xxxxM DoP: 1320-2231 B2ca, s1, d1, a1 NB0598 Communications supply in-/outdoor (MM=month, YY=year)																																						
G									G																														
F	<table><tr><th colspan="2">Specifications Heat Shrink Tubing (B,C)</th></tr><tr><td>Length</td><td>80mm</td></tr></table>								Specifications Heat Shrink Tubing (B,C)		Length	80mm	F																										
Specifications Heat Shrink Tubing (B,C)																																							
Length	80mm																																						
E	<table><tr><th colspan="2">Specifications Fanout cable (D,E)</th></tr><tr><td>Type</td><td>Tubing</td></tr><tr><td>Outer diameter</td><td>0.9mm</td></tr><tr><td>Operation temp.</td><td>-20°C to +70°C</td></tr><tr><td>Storage temp.</td><td>-40°C to +85°C</td></tr><tr><td>Colors</td><td>Blue, Orange, Green, Brown, Gray, White, Red, Black, Yellow, Purple, Pink, Aqua</td></tr><tr><td>Cable marking</td><td>1 to 24</td></tr><tr><td>Fanout length</td><td>500mm (+50mm-0mm) - 940mm (+50mm-0mm)</td></tr><tr><td>Fanout staggered increments</td><td>40mm</td></tr></table>								Specifications Fanout cable (D,E)		Type	Tubing	Outer diameter	0.9mm	Operation temp.	-20°C to +70°C	Storage temp.	-40°C to +85°C	Colors	Blue, Orange, Green, Brown, Gray, White, Red, Black, Yellow, Purple, Pink, Aqua	Cable marking	1 to 24	Fanout length	500mm (+50mm-0mm) - 940mm (+50mm-0mm)	Fanout staggered increments	40mm	E												
Specifications Fanout cable (D,E)																																							
Type	Tubing																																						
Outer diameter	0.9mm																																						
Operation temp.	-20°C to +70°C																																						
Storage temp.	-40°C to +85°C																																						
Colors	Blue, Orange, Green, Brown, Gray, White, Red, Black, Yellow, Purple, Pink, Aqua																																						
Cable marking	1 to 24																																						
Fanout length	500mm (+50mm-0mm) - 940mm (+50mm-0mm)																																						
Fanout staggered increments	40mm																																						
D									D																														
C	<table><tr><th colspan="2">Specifications Connector (F,G)</th></tr><tr><td>Connector</td><td>LC</td></tr><tr><td>Polishing Connector</td><td>UPC</td></tr><tr><td>Ferrule Connector</td><td>Ceramic Zirconia (ZrO2)</td></tr><tr><td>Ferrule Diameter</td><td>1.25mm</td></tr><tr><td>Housing</td><td>Blue (PC)</td></tr><tr><td>Boot</td><td>White (TPV)</td></tr><tr><td>Cap</td><td>White(PE)</td></tr></table>								Specifications Connector (F,G)		Connector	LC	Polishing Connector	UPC	Ferrule Connector	Ceramic Zirconia (ZrO2)	Ferrule Diameter	1.25mm	Housing	Blue (PC)	Boot	White (TPV)	Cap	White(PE)	C														
Specifications Connector (F,G)																																							
Connector	LC																																						
Polishing Connector	UPC																																						
Ferrule Connector	Ceramic Zirconia (ZrO2)																																						
Ferrule Diameter	1.25mm																																						
Housing	Blue (PC)																																						
Boot	White (TPV)																																						
Cap	White(PE)																																						
B									B																														
A	<table><tr><td rowspan="3"></td><td colspan="7">ACT Singlemode Fiber Optic Indoor / Outdoor cable 9/125 OS2</td></tr><tr><td colspan="5">Item : RL44xx</td><td colspan="2">Revision : 1.1</td></tr><tr><td colspan="5"></td><td colspan="2">Date : 16-04-2024</td></tr><tr><td colspan="8">This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.</td><td>A</td></tr></table>									ACT Singlemode Fiber Optic Indoor / Outdoor cable 9/125 OS2							Item : RL44xx					Revision : 1.1							Date : 16-04-2024		This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.								A
	ACT Singlemode Fiber Optic Indoor / Outdoor cable 9/125 OS2																																						
	Item : RL44xx					Revision : 1.1																																	
						Date : 16-04-2024																																	
This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.								A																															
	8	7	6	5	4	3	2	1																															



Thickest part of assembly

Item	Length(m)	Item	Length(m)
RL4435	5	RL4416	160
RL4401	10	RL4417	170
RL4402	20	RL4418	180
RL4403	30	RL4419	190
RL4404	40	RL4420	200
RL4405	50	RL4421	210
RL4406	60	RL4422	220
RL4407	70	RL4423	230
RL4408	80	RL4424	240
RL4409	90	RL4425	250
RL4410	100	RL4426	260
RL4411	110	RL4427	270
RL4412	120	RL4428	280
RL4413	130	RL4429	290
RL4414	140	RL4430	300
RL4415	150		

Specifications heat shrink tubing (1)	
Length	60mm
Specifications protective tube (2)	
Material	PVC
Color	Transparent
Dimensions	1120mm(+50mm -0mm) x 15mm x 18mm

Length (m)	Reel Weight (KG)	Reel dimension (mm)
120	1.7	327 (H) x 345 (ø)
121-240	1.9	327 (H) x 400 (ø)
241-330	2.8	330 (H) x 450 (ø)
331-420	3.1	330 (H) x 480 (ø)
≥421	3.3	400 (H) x 480 (ø)



Drawn by : M. Diks

ACT Singlemode Fiber Optic Indoor / Outdoor cable 9/125 OS2

Item : RL44xx

Revision : 1.1

Date : 16-04-2024

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, printed or electronic, are uncontrolled and intended only for immediate use.

Specifications fiber	
Fiber type	Singlemode
Fiber class	OS2
Category	G.657A2
Diameter core / cladding	9/125
Specifications optical performance	
Insertion Loss (IL) typical	0.1 dB
Insertion Loss (IL) maximum	0.15 dB
Return Loss (RL)	≥ 55 dB
Standard compliances	
IEC 61754-20	Fibre optic connector interfaces - Type LC connector family
IEC 61300-3-47	Examinations and measurements - End face geometry of PC/APC spherically polished ferrules using interferometry
IEC 60794-2-20	Indoor cables - Family specification for multi-fibre optical cables
IEC 60794-1-2	Basic optical cable test procedures
IEC 60332-1-2	Test for vertical flame propagation for a single insulated wire or cable
IEC 60754-1	Determination of the halogen acid gas content
IEC 60754-2	Determination of acidity (by pH measurement) and conductivity
IEC 61034-2	Measurement of smoke density of cables burning under defined conditions



Drawn by : M. Diks

ACT Singlemode Fiber Optic Indoor / Outdoor cable 9/125 OS2

Item : RL44xx

Revision : 1.1

Date : 16-04-2024

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, printed or electronic, are uncontrolled and intended only for immediate use.