



Recommend P.C.B Layout

TABLE B

HM-19F4-25	HDMI 19PIN (F) SMT TYPE FLANGE1.1	15u"/GOLD 15u"
HM-19F4-08	HDMI 19PIN (F) SMT TYPE FLANGE1.1	30u"/GOLD 30u"
Part No.	DESCRIPTION	PLATING

NOTES:

Material

Housing: LCP, UL 94V-0 Rated; Color: Black.
 Shield: Brass.
 Plating: Tin
 Contact: Phosphor Bronze
 Plating: Gold Plating "Table B" Over Tin on Contact Area;
 Tin Plating on Solder Area.

Electrical

Contact resistance: Contact 30m ohm max.
 Shell 50m ohm max.
 Insulation resistance: unmated 100M ohm min.
 mated 10M ohm min.
 Dielectric strength: 500 VAC min.
 Current rating: 0.5A min.

BOM	
19	CONTACT
1	SHELL
1	HOUSING
數量	零件

REV.	DESCRIPTION	CHANGE. BY	APPVL. BY	DATE
△C				
△B	修改外觀,尺寸變更	REN	Frank	12/06/07"
△A	修改端子尺寸	REN	Frank	11/23/07"

繪圖 DRAW. BY	Vincent	日期 DATE	06"/12/04	單位 UNIT	mm	一般公差	.x ±0.25 .xx ±0.10	JKL TECHNOLOGY CO., LTD.	品名 ITEM	HDMI 19PIN (F) SMT TYPE FLANGE1.1			SHEET
核準 APPVL. BY	Frank	版本 VERSION	B	比例 SCALE	1:1				料號 PART NO.	TABLE B	圖號 DWG NO.	QC1765	SIZE A4