


Parallel-Verbinder

Parallel splices

Lötfreie Parallel-Verbinder mit Polyamid-Hülsen

Solderless parallel splices, Polyamide insulated




Material: SE-Cu, galv. verzinkt
Material: electrolytic copper, electro-tinned

Kennfarbe Isolation Colour code insulation	Artikel-Nummer Part number	Leiter- querschnitt Wire size mm ² AWG	S	Abmessungen mm Dimensions mm				Verp.-Einh. Stück Standard packing Piece
				Ø d 1	Ø d 4	L 1	L 2	
gelb yellow	EHY 524-0,5	0,1-0,5 26-22	0,4	1,2	2,0	5	13	2000
rot red	EHY 450-1	0,5-1,5 20-16	0,8	1,6	3,4	7	17	1000
blau blue	EHY 451-2,5	>1,5-2,5 16-14	0,8	2,3	4,0	7	17	1000
gelb yellow	EHY 452-6	>4-6 10	1,0	3,6	5,6	7	21	1000

Lötfreie Parallel-Verbinder mit Polyamid-Hülsen, aufgeweitete Form

Solderless parallel splices, Polyamide insulated, flared version



Material: SE-Cu, galv. verzinkt
Material: electrolytic copper, electro-tinned

Kennfarbe Isolation Colour code insulation	Artikel-Nummer Part number	Leiter- querschnitt Wire size mm ² AWG	S	Abmessungen mm Dimensions mm				Verp.-Einh. Stück Standard packing Piece
				Ø d 1	Ø d 4	L 1	L 2	
rot red	EHY 450.40-1	0,5-1,5 20-16	0,8	1,6	4,0	7	17	1000
blau blue	EHY 451.51-2,5	>1,5-2,5 16-14	0,8	2,3	5,1	7	17	1000