



Lötfreie Flachsteckhülsen mit PVC-Isolation Solderless receptacles, PVC insulated


Kennfarbe Isolation Colour code insulation	Artikel-Nummer Part number	ähnlich similar to DIN 46245	Leiter- querschnitt Wire size mm² AWG	Steck- dicke Tab thickness mm	Abmessungen mm Dimensions mm				Verp.-Einh. Stück Standard packing Piece
					Ø d 1	Ø d 4	L 1	L 2	
rot red	RSP 7506 F 2,8-1	●	0,5-1,5 20-16	0,8	1,6	4,3	18,8	14,7	1000
rot red	RSP 7506.001 F 2,8-1	●	0,5-1,5 20-16	0,5	1,6	3,2	18,0	14,7	1000
gelb yellow	RSP 7509 F 9,5-6		>4-6 10	1,2	3,6	6,2	29,2	22,5	500
rot red	RSP 7503 F 4,8-1	●	0,5-1,5 20-16	0,8	1,6	4,4	19,3	16,9	1000
rot red	RSP 7503.001 F 4,8-1		0,5-1,5 20-16	0,5	1,6	3,2	19,3	15,0	1000
blau blue	RSP 7504 F 4,8-2,5	●	1,5-2,5 14	0,8	2,3	4,8	19,0	16,8	1000
blau blue	RSP 7504.001 F 4,8-2,5		1,5-2,5 14	0,5	2,3	3,8	19,0	14,5	1000
rot red	RSP 7500 F 6,3-1	●	0,5-1,5 20-16	0,8	1,6	4,3	21,0	19,0	1000
blau blue	RSP 7501 F 6,3-2,5	●	1,5-2,5 14	0,8	2,3	4,8	21,0	19,0	1000
gelb yellow	RSP 7502 F 6,3-6	●	>4-6 10	0,8	3,4	5,4	22,0	17,5	500



Material: CuZn, galv. verzinkt
Material: CuZn, electro-tinned

Lötfreie Flachstecker mit PVC-Hülsen Solderless tabs, PVC insulated

Kennfarbe Isolation Colour code insulation	Artikel-Nummer Part number	DIN	Leiter- querschnitt Wire size mm² AWG	Steck- dicke Tab thickness mm	Abmessungen mm Dimensions mm				Verp.-Einh. Stück Standard packing Piece
					Ø d 1	Ø d 4	L 1	L 2	
rot red	RSP 7510 Z 6,3-1		0,5-1,5 20-16	0,8	1,6	3,5	21,7	16,0	1000
blau blue	RSP 7511 Z 6,3-2,5		>1,5-2,5 14	0,8	2,3	4,3	22,7	16,0	1000



Material: CuZn, galv. verzinkt
Material: CuZn, electro-tinned