



## 3G/HD/SD-SDI Distribution Amplifier

Model 1T-DA-726

### 1T-DA-726 3G/HD/SD-SDI Distribution Amplifier

provides 6 outputs from a single SDI input for distribution to devices capable of receiving and/or displaying such signals. The 1T-DA-726 3G/HD/SD-SDI Distribution Amplifier provides third generation HD/SD signal distribution with triple-rate processing and six separately buffered and reclocked outputs. Data Rates of 270, 1483, 1485 and 2970 Mbps support DVB-ASI standards, as well as SMPTE 259M, 292M, 424M and 425M protocols. Automatic input cable equalization up to 300m (1000ft)@SD and 150m (500ft)@HD/3G is utilized. All ancillary data is passed through to the outputs, and since the SDI signals are reclocked, multiple 1T-DA-3G/HD/SD-SDI Distribution Amplifiers can be cascaded for longer transmission runs. Front panel LEDs indicate that DC power is present and signal lock/reclocking is in progress. Finally, the TV One exclusive locking power connector prevents inadvertent loss of DC power to the device.

### Specifications

#### Video Inputs

3G/HD/SD-SDI 1x via BNC Connector

#### Video Output

3G/HD/SD-SDI 6x via BNC Connector

#### SDI Transport

SDI Standards 3G/HD/SD-SDI

Data Rates 270 / 1483 / 1485 / 2970 Mbps

Video Bandwidths [2.97Gbps & 2.97/1.001Gbps]

Supported Protocols DVB-ASI@270Mbps, SMPTE

259M,292M,424M,425M

Signal Reclocking All Outputs

Ancillary Data Pass-thru, All Outputs

I/O Impedance 75Ω

#### Eye Pattern (HD)

Amplitude 800mv (<10%)

Rise Overshoot <2% (<10%)

Fall Overshoot <2% (<10%)

Long Time Jitter 0.195usec (<1.0usec)

Timing Jitter 0.8usec (<1.0usec)

Alignment Jitter 0.13usec (<0.2usec)

#### Max Cable Distances

Reference: Belden 3G:150m(500'), HD:150m(500'),

1694A SD:300m(1000')



### Key Features of the 1T-DA-726

- 3G/HD/SD Triple Rate Signal Processing
- Six Buffered and Reclocked Outputs
- Data Rates of 270 / 1483 / 1485 / 2970 Mbps
- Protocols DVB-ASI, SMPTE 259M,292M,424M,425M
- Automatic Cable Equalization and Signal Retiming
- All Ancillary Data is passed to the outputs
- DAs may be Cascaded for Longer Cable Runs
- Front Panel Input Signal Lock and Rate LED
- Locking DC Power Connector

### Warranty

Limited Warranty

3 Years Parts and Labor

### Mechanical

Size (H-W-D)

30x200x90mm(1.18"x7.88"x3.54")

Weight (Net)

530g (1.17lbs)

### Environmental

Operating Temperature

0° to +40°C (+32° to +104°F)

Operating Humidity

20% to 90%, Non-condensing

Storage Temperature

-20° to +60°C (-4° to +140°F)

Storage Humidity

20% to 90%, Non-condensing

### Power Requirement

External Power Supply

5VDC@6A

### Regulatory Approvals

SDI DA

FCC, CE, RoHS

Power Supply

UL, CUL, CE, PSE, GS, RoHS

### Accessories Included

1x AC Power Adapter

US, UK or Euro

1x Instruction Manual

### Product Item Number

1T-DA-726

1x6 3G/HD/SD-SDI DA

### Panel Drawings

