

This safety data sheet meets the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Date of issue 2019-10-15

Version 1

Section 1: IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE MANUFACTURER

1.1. Product identification

Product code K6020
Product name Intronics KONTAKT 60 200ML KC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaners - Precision
Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Supplier Intronics B.V
P.O. box 123, 3770 AC Barneveld
the Netherlands

For more information, please contact:

Technical support: +31 34 24 07 050

1.4 Emergency contact:

CRC Industries Europe, Belgium: Tel .: +32 (0) 52 / 45.60.11 (office hours)
the Netherlands: National poisoning information center: 030 274 88 88 (Only for professional emergency workers)
Belgium: Poison Center: 070 - 245 245

Section 2: HAZARD IDENTIFICATION

2.1. Classification of the substance or mixture



Regulation (EC) No 1272/2008

Physical: Aerosols, category 1
Extremely flammable aerosol.
Pressurised container: May burst if heated.
Classification is based on test data.

Health: Skin irritation, category 2
Causes skin irritation.
Eye irritation, category 2
Causes serious eye irritation.
Specific target organ toxicity - single exposure, category 3
May cause drowsiness or dizziness.
Classification based on calculation method.

Environment: Hazardous to the aquatic environment, chronic category 3 Harmful to aquatic life with long lasting effects

2.2. Label elements

Product identifier:	Contains: hydrocarbons propan-2-ol; isopropyl alcohol ;isopropanol
Hazard pictogram(s):	 
Signal word:	Danger
Hazard statement(s):	H222 : Extremely flammable aerosol. H229 : Pressurised container: May burst if heated. H315 : Causes skin irritation. H319 : Causes serious eye irritation. H336 : May cause drowsiness or dizziness. H412 : Harmful to aquatic life with long lasting effects.
Precautionary statement(s):	P102 : Keep out of reach of children. P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 : Do not spray on an open flame or other ignition source. P251 : Do not pierce or burn, even after use. P261 : Avoid breathing dust/fume/gas/mist/vapours/spray. P271 : Use only outdoors or in a well-ventilated area. P410/412 : Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501-2 : Dispose of contents/container to an authorised waste collection point.
Supplemental Hazard information:	None

2.3. Other hazards

no information available

Section 3: COMPOSITION AND INFORMATION ON INGREDIENTS

3.1 Substances / 3.2 Mixtures

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
propan-2-ol; isopropyl alcohol ;isopropanol	01-2119457558-25	67-63-0	200-661-7	25-50	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3	H225,H319,H336	B
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	01-2119475514-35	-	(921-024-6)	<25	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2	H225,H315,H336,H304,H411	B,Q
butan-2-ol	01-2119475146-36	78-92-2	201-158-5	<20	Flam. Liq. 3, Eye Irrit. 2, STOT SE 3, STOT SE 3	H226,H319,H335,H336	B
white mineral oil (petroleum)	01-2119487078-27	8042-47-5	232-455-8	5-10		-	B
carbon dioxide	-	124-38-9	204-696-9	1-5	Press. Gas	H280	A,G

Explanation notes

A : substance with Community workplace exposure limit

B : substance with national established workplace exposure limit

G : exempted from the obligation to register in accordance with art.2(7) of REACH Regulation No 1907/2006

Q : The CAS-no is only an indicative identifier to be used outside the EU for global inventory entries.

(* Explanation phrases : see chapter 16)

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

- Contact with eyes :** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- Contact with skin :** Take off contaminated clothing and wash before reuse. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.
- Inhalation :** IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- Ingestion :** If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention

4.2. Most important acute and delayed symptoms and effects

- Inhalation :** Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
- Ingestion :** After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. Symptoms : sore throat, abdominal pain, nausea, vomiting
- Skin contact :** Irritating to skin Symptoms : redness and pain
- Eye contact :** Irritating to eyes Symptoms : redness and pain, impaired vision

4.3. Indication of the requirement for immediate medical attention and special treatment

- General Advice** If you feel unwell, seek medical advice (show the label where possible If symptoms persist always call a doctor.

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing material

- Suitable extinguishing material** foam, carbon dioxide or dry agent
- Unsuitable extinguishing material** Do not use water jet extinguishing media, due to the risk of spreading fire.

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C Forms hazardous decomposition products CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fume

Section 6: MEASURES FOR THE ACCIDENTAL RELEASE OF THE SUBSTANCE**6.1. Personal precautions, protective equipment, and emergency procedures**

Shut off all ignition sources
Ensure adequate ventilation
Wear suitable protective clothing and gloves.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses
If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material
Place in appropriate container
This material and/or its container must be disposed of as hazardous waste.

6.4. Reference to other sections

For further information see section 8

Section 7: HANDLING AND STORAGE**7.1. Precautions for safe handling of the substance or mixture**

Keep away from heat and sources of ignition
Take precautionary measures against static discharges
Equipment should be earthed
Use explosion-proof electrical/ventilating/lighting/.../equipment.
Use only non-sparking tools.
Do not breathe aerosols or vapours.
Ensure adequate ventilation
Avoid contact with skin and eyes.
Wash thoroughly after use
Wear protective gloves/protective clothing/eye protection/face protection.
Eyewash bottles should be available

7.2. Conditions for safe storage, including incompatible products

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.
Keep out of reach of children.

7.3. Specific end use

Cleaners – Precision

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

Hazardous ingredient	CAS-nr.	method	
EU established exposure limits:			
carbon dioxide	124-38-9	TWA	9000 mg/m3
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	STEL	1800 mg/m3
		TWA	400 ppm
		STEL	500 ppm
National established exposure limits, United Kingdom			
carbon dioxide	124-38-9	TWA	5000 ppm
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	STEL	15000 ppm
		TWA	400 ppm
		STEL	500 ppm
butan-2-ol	78-92-2	TWA	100 ppm
		STEL	150 ppm

8.2. Measures to control exposure

Control procedures

Ensure adequate ventilation
 Keep away from heat and sources of ignition
 Take precautionary measures against static discharges

Personal protection

Take precautions to avoid contact with skin and eyes when handling the product.
 Ensure adequate ventilation
 In all cases handle and use the product in accordance with good industrial hygiene practices.

Inhalation

In case of insufficient ventilation, wear suitable respiratory equipment.

recommended respiratory protection: hands and skin

Air purifying respirator equipped with organic gas/vapor cartridge (type AX)
 When handling the product wear chemical-resistant gloves (standard EN 374).

Recommended gloves

Nitrile
 The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Depending on amount and duration of use and the risk of contact with the product the gloves manufacturer can assist you in the selection of the right glove material and breakthrough time

eyes

Wear safety eyewear according to EN 166.

Environmental protection

Avoid release to the environment.
 Collect spillage.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information about basic physical and chemical properties**

(for aerosols data for the product without propellant)

Apperance :	CO2 propelled liquid.
colour :	Red.
odour :	Solvent.
pH :	Not applicable.
Boiling point/range :	Not available.
Flash point :	< 0 °C (Closed Cup)
Evaporation rate :	Not available.
Explosion limits :	Not available.
lower limit :	Not available.
Vapour pressure :	Not available.
Relative density :	0.76 g/cm ³ (@ 20°C).
Solubility in water :	Miscible with water
Auto-ignition :	> 200 °C
Viscosity :	Not applicable

9.2. Other information

VOC = volatile organic compounds 640 g/l

Section 10: STABILITY AND REACTIVITY**10.1. Reactivity**

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possible hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO₂

Section 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

acute toxicity:	based on available data the classification criteria are not met
skin corrosion/irritation:	Causes skin irritation

serious eye damage/irritation: Causes serious eye irritation.

skin sensitisation: based on available data the classification criteria are not met

germ cell mutagenicity: based on available data the classification criteria are not met

carcinogenicity: based on available data the classification criteria are not met

toxicity for reproduction: based on available data the classification criteria are not met

STOT-single exposure: May cause drowsiness or dizziness.

STOT repeated exposure: based on available data the classification criteria are not met

aspiration hazard: based on available data the classification criteria are not met

Information on likely routes of exposure:

Inhalation : Inhalation of solvent vapours may give rise to nausea, headaches and dizziness

Ingestion : May cause gastrointestinal disturbances

Skin contact : May cause irritation.

Eye contact : Irritating to eyes

Toxicological data :

Hazardous ingredient	CAS-nr.	method	
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	LD50 oral rat	5840 mg/kg
butan-2-ol	78-92-2	LC50 inhal.rat	> 25000 mg/l
		LD50 derm.rabit	13900 mg/kg
		LD50 oral rat	> 2000 mg/kg
white mineral oil (petroleum)	8042-47-5	LD50 derm.rabit	> 2000 mg/kg
		LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 5 mg/l
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	-	LD50 derm.rabit	> 2000 mg/kg
		LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 25000 mg/m3
		LD50 derm.rat	> 2000 mg/kg

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Hazardous to the aquatic environment, chronic category 3

Harmful to aquatic life with long lasting effects

Hazardous ingredient	CAS-nr.	method	
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	IC50 algae	1000 mg/l
butan-2-ol	78-92-2	LC50 fish	9640 mg/l
		EC50 daphnia	9714 mg/l
		IC50 algae	2029 mg/l
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	-	LC50 fish	2993 mg/l
		EC50 daphnia	308 mg/l
		LC50 fish	> 10 mg/l
		EC50 daphnia	3 mg/l

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulation

No information available.

12.4. Mobility in the soil

No experimental data available

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other harmful effects

No experimental data available

Section 13: DISPOSAL INSTRUCTIONS**13.1. Waste treatment methods**

Product : This material and its container must be disposed of in a safe way.
Do not discharge into drains or the environment, dispose to an authorised waste collection point.

Contaminated packaging : Disposal should be in accordance with local, state or national legislation

Section 14: INFORMATION REGARDING TRANSPORT

14.1 UN / ID No	UN-number : 1950
14.2 Proper shipping name	AEROSOLS
14.3 Hazards class	Class: 2.1
	ADR/RID - Classification code: 5F
14.4 Packing group	Not applicable.
14.5 Harmful to the environment	ADR/RID - Environmentally hazardous: No
Marine pollution	IMDG : No IATA/ICAO - Environmentally hazardous: No
14.6 Special Provisions	ADR/RID - Tunnelcode: (D)
	IMDG - Ems: F-D, S-U
	IATA/ICAO - PAX: 203
	IATA/ICAO - CAO 203
14.7 Transport in bulk	No information available
in accordance with Annex II to	
MARPOL 73/78 and the IBC code	

Section 15: REGULATION**15.1. Specific safety, health and environmental regulations and legislation for the substance or mixture****European Union**

The Safety Data Sheet is compiled according to the current European requirements.

Regulation (EC) No 1907/2006 (REACH)

Regulation (EC) No 1272/2008 (CLP)

Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

15.2. Chemical safety assessment

Chemical safety assessment No information available


Section 16: OTHER INFORMATION**An explanatory list of abbreviations and acronyms used in the safety data sheet**

*Explanation hazard statements: H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H280 : Contains gas under pressure; may explode if heated.
H304 : May be fatal if swallowed and enters airways..
H315 : Causes skin irritation.
H319 : Causes serious eye irritation.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H411 : Toxic to aquatic life with long lasting effects

acronyms and synonyms: TWA = time weight average
STEL = short time exposure limit
VOC = volatile organic compounds
PBT = persistent bioaccumulative toxic
vPvB = very persistent very bioaccumulative

Date of issue 2019-10-15**Revision date** Not applicable.**Reason for revision:** Not applicable.**This safety data sheet is in accordance with the requirements of Regulation (EC) 1907/2006****Disclaimer**

The information in this SDS is prepared to the best of our ability and reflects the state of knowledge at the time of publication. The data is presented as a guideline for the safe handling, use, storage, transport, and disposal of the substance, and cannot be regarded as a guarantee certificate or quality specification. The information given relates to the substance as such and may no longer be valid when the substance is used together with other substances or in processes.

End of the safety data sheet**Intronics BV**Shardene Brink, *compliance officer*
.....
SIGNATURE