

Mini Cat5 VGA+Audio Extender User Manual

(Model: MBS-M150)


Features:

1. Extend VGA+Audio signal over single Cat5e/6(UTP 24AWG) cable
2. Resolution: 1600x1200 Max.
3. Distance: 150M Max.
4. Support Plug & Play, no software required
5. User adjustable Equalization for optimum video quality
6. Transmitter(MBS-M150T) is powered by USB port
7. Mini size and easy to install

Package Content:

Transmitter(MBS-M150T) x 1, Receiver(MBS-M150R) x 1, AC 7.5V Power Adapter x 1, User Manual x 1

Installation:



1. Please turn off the VGA output device and VGA displays.
2. Connect MBS-M150T to VGA out, audio out and USB ports of a PC or VGA output device.
3. Connect MBS-M150R to remote VGA display and speaker.
4. Connect the RJ45 port of MBS-M150T and MBS-M150R with Cat5e/6 cable (1:1 pin-out).
5. Connect AC 7.5V power adapter to MBS-M150R.
6. Turn on your VGA display and VGA output device.

7. Tune the "EQ" of MBS-M150R to get optimum video quality.
8. If MBS-M150T can not detect an active VGA signal, the LED of RJ45 jack will blink.

Remarks:

1. Please read this manual carefully before installing the extender.
2. Please use high quality Cat5e/6 cables for optimum operation. If the RGB delay skew is too big, please use our CAT5 VGA EXTENSION cable(Item# CWIN-UTP24) or BELDEN CAT5E cable(Item# 1700A) to improve.
3. To prevent potential power damage, please use 3-wire power cords for PC and monitors and ensure AC outlets at PC and monitors are on the same phase and have correct grounding.
4. One year limited warranty.

Trademarks:

All the companies, brand names and product names referred to this manual are the trademarks or registered trademarks belonging to their respective companies.