


1		2		3		4		5		6		7		8	
ALTW CONFIDENTIAL 2015-10-09 R&D DEPT. Connector 1 Female Nut 2 Nut 3 O-ring 7 Clamp Ring 4 Seal 5 Sealing Nut 6 Pin Assignments Front View				REV.		ECN NO.		DATE		SIGN		DESCRIPTION			
				A		Initial Release		2015/10/09		Mila		Change Rev.01 To Rev.A			
ALTW DCC. DEPT. CONFIDENTIAL 2015.10.28 ISSUED															
UNIT:mm				TITLE				ITEM NO		DRAWN BY		DATE			
TOLERANCE		±0.5mm		MI2 D-Code Unshielded Assy 4PIN F Conn. F Pin				MI2D-04BFFB-SL700I		Mila		2015-10-09			
				SCALE		SIZE		SHEET		CHECKED BY		DATE			
				1:1		A4		1 OF 2		Cary		2015-10-09			
				REV.		WC-REV.		QC:Inspection item		APPROVED BY		DATE			
				A		A.2				Jerry		2015-10-09			
								CUSTOMER		ALTW					
												8 FNN10702-01-02A1			

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.



M 12D - 04 B F F B - S L 7 001

12D: D-Code

04: 4Pin

B: Without S/R(無網尾)

F: Female Connector(母座)

F: Female Pin(母Pin)

001: Without Cable

7: IP67(防水等級67)


L: Straight(180°)

S: Screw(螺紋式)

B: Screw in Type(組裝式)

Note:

- * Important Dimension To Check.
- * Waterproof Rate: IP67
- * Housing: Nylon, Black
- * Female Pin: Copper Alloy, Gold Plated
- * Female Nut: Zinc Alloy, Nickel Plated
- * Nut: PBT+PC, Black
- * O-Ring: Silicon, Grey
- * Clamp Ring: Nylon, Black
- * Sealing Nut: PBT+PC, Black
- * Seal: Silicon, Grey
- * Seal For Cable OD: $\varnothing 4.0\text{mm} \sim \varnothing 8.0\text{mm}$
- * Screws for Wire connection recommended
tightening torque: $0.61 \sim 0.84 \text{ kgf.cm} / 0.059 \sim 0.082 \text{ N.m}$
- * Applicable Wire gauge (Stranded wire cross section)
 $0.14\text{mm}^2 (26\text{AWG}) \sim 0.82\text{mm}^2 (18\text{AWG})$
- * Mating Recommended tightening torque:
 $3 \sim 4 \text{ kgf.cm} / 0.29 \sim 0.39 \text{ N.m}$
- * Sealing-Nut Recommended tightening torque:
 $4 \sim 6 \text{ kgf.cm} / 0.39 \sim 0.59 \text{ N.m}$
- * Detailed applicable wire specifications may vary
depending on the actual wire construction.



UNIT:mm		TITLE M12 D-Code Unshielded Assy 4PIN F Conn. F Pin		
TOLERANCE ±0.5mm		SCALE 1:1	SIZE A4	SHEET 2 OF 2
		REV. A	WC-REV. A.2	 :Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	M12D-04BFFB-SL7001	DRAWN BY	Mila	DATE	2015-10-09
DWG NO	M12D-04BFFB-SL7001	CHECKED BY	Cary	DATE	2015-10-09
CUSTOMER	ALTW	APPROVED BY	Jerry	DATE	2015-10-09