

Features and Benefits

The PowerCat 6A Shielded Cable is a key component of the PowerCat 6A end-to-end solution.

Molex PowerCat 6A U/FTP Cable is specifically designed to support high speed data network applications such as 10-Gigabit Ethernet (10GBASE-T). The cable is constructed of 4 screened pairs and a drain wire. This cable minimises alien crosstalk, provides excellent signal isolation and provides superior electromagnetic interference (EMI) protection.

Molex recommends that the full range of PowerCat 6A Shielded products be used in a system to maximise cabling performance. This system is compliant with ISO/IEC 11801 amendment 1 and TIA/EIA 568.2-10 for the support of 10GBASE-T.

- Outstanding signal isolation
- The cable is compliant with ISO/IEC 11801 amendment 2 and TIA/EIA 568-C.2
- Enhanced performance 4 pair U/FTP LS0H cable
- Resistant to alien crosstalk
- Colour coded for ease of termination
- Reaction to Fire Euroclass: Dca-s2,d1,a1

Commercial Standards

ISO/IEC 11801 amendment 2:2010
TIA/EIA-568-C.2 Category 6A
IEC 61156-5
Intertek ETL verified
RoHS Compliant

Fire Propagation Tests

EU Regulation 305/2011 (CPR)
EN 50575:2014+A:2016
Euroclass Dca-s2,d1,a1
DoP No: MLXCES-2017-C-011 located on web
<http://www.molexces.co.uk/about-us/our-compliance/cpr/dop-certificates/>

Applications

Category 6A U/FTP Cable is intended for high speed data applications up to 500MHz including:

IEEE 802.3 10GBASE-T 10Gb/s
IEEE 802.3 1000BASE-T 1Gb/s
TIA/EIA-854 1000BASE-TX 1Gb/s
ATM 155Mb/s 155Mb/s

Technical Information

Mechanical Characteristics

Conductor Size: 23AWG
Primary Insulation: Polyolefin
Screen material: Laminated Aluminium
Sheath Type: LS0H
Nominal OD: 6.8mm nom.
NVP: 75-77%
Screen: Each pair enclosed in laminated aluminium foil
Drain Wire: tin-coated copper
Pulling Force: 100N maximum
Short term. bend radius: 8 x OD mm
Long Term bend radius: 4 x OD mm
Operating Temperature
Storage: -20°C to +75°C
Operation: 0°C to +60°C
Sheath Colour: Violet RAL 4005

Electrical/Optical Characteristics

Capacitance: 40 pF/m nom. @1 KHz.
DC Resistance: 72 Ω/Km max.
Propagation Delay: 514 + 36f^{1/2} nS/100m max @1-500 MHz
Propagation Delay Skew: 45 nS/100 max @ 1-500 MHz
Mean Impedance: 100Ω ± 6 @ 1-500 MHz
Voltage Rating: 2V dc maximum
Resistance Unbalance: 2% max.
Coupling Attenuation: IEC 61156-5 Type II
Weight per 500m reel: 25.4kg



MOLEX CONNECTED ENTERPRISE SOLUTIONS

Americas
Tel: 630 969 4550
www.molexces.com

EMEA
Tel: 44 (0)2392 205800
www.molexces.co.uk

APAC
Tel: 61 3 9971 7111
www.molexces.com

Transmission Properties and Electrical Specifications

FREQ MHz	Insertion Loss dB/100m Max.	NEXT dB Min.	PS NEXT dB Min.	EL FEXT dB/100m Min.	PS ELFEXT dB/100m Min.	RL dB Min.	DELAY nS/100m Max.	TCL dB Min.	EL-TCL dB Min.	PS AN- EXT dB Min.	PS AACRF dB Min.
1	2.0	74.3	72.3	67.8	64.8	20.0	570	40.0	35.0	67.0	67.0
10	5.9	59.3	57.3	47.8	44.8	25.0	545	40.0	15.0	67.0	58.2
20	8.3	54.8	52.8	41.8	38.8	25.0	542	37.0	9.0	67.0	52.2
25	9.3	53.3	51.3	39.8	36.8	24.3	541	36.0	7.0	67.0	48.7
30	10.2	52.1	50.1	38.3	35.3	23.8	541	35.2	5.5	67.0	48.7
62.5	14.9	47.4	45.4	31.9	28.9	21.5	539	32.0	NS	65.6	42.3
100	19.0	44.3	42.3	27.8	24.8	20.1	538	30.0	NS	62.5	38.2
200	27.5	39.8	37.8	21.8	18.8	18.0	537	27.0	NS	58.0	32.2
250	31.0	38.3	36.3	19.8	16.8	17.3	536	26.0	NS	56.5	30.2
300	34.2	37.1	35.1	18.3	15.3	16.8	536	25.2	NS	55.3	28.7
400	40.0	35.3	33.3	15.8	12.8	15.9	536	24.0	NS	53.5	26.2
500	45.3	33.8	31.8	13.8	10.8	15.2	536	23.0	NS	52.0	24.2

ORDERING INFORMATION

Order No.	SAP No.	Description
CAA-0322L-VL	183020029	PowerCat 6A U/FTP LS0H Cable Dca-s2,d1,a1 violet 500m reel



MOLEX CONNECTED ENTERPRISE SOLUTIONS

Americas
Tel: 630 969 4550
www.molexces.com

EMEA
Tel: 44 (0)2392 205800
www.molexces.co.uk

APAC
Tel: 61 3 9971 7111
www.molexces.com



Connected Enterprise Solutions



Declaration of Performance

DoP No:

MLXCES-2017-C-011

Unique Identification code & description of the product type:

CAA-0322L-VL

183020029

U/FTP C6A LSZH

Intended use:

Data communications cable for use in construction works subject to reaction to fire requirements.

Manufacturer:

Molex Connected Enterprise Solutions Sp. z o.o.

83-112 Lubiszewo

ul. Tczewska 2 Rokitki

Poland

Assessment and Verification of Consistency of Performance (AVCP) system:

AVCP:3

Harmonised Standard

EN 50575:2014+A1:2016

Notified Product Certification Body Name and Reference No.

CEIS:1722

Declared Performance:

Reaction to Fire Euroclass:

Dca,s2,d1,a1

Dangerous Substances: No Performance Declared.

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Carol Harris
Position: Product Manager
Place: UK
Date: 1-6-2017

Web address of the DoP : <http://www.molexc.es.com/about-us/our-compliance/cpr/>

English