NCNU-H04 / NCNU-G04 Rextron



LAN USB 2.0 Converter

Specifications

Function	NCNU-H04	NCNU-G04
Signal Input	USB 2.0 (1.0 Compatible)	
Signal Output	Ethernet	Ethernet
Speed	10 / 100 Mbps	10 / 100 / 1000 Mbps
LEDs	Dual Color x 1	
Connector (In)	USB-A x 4	
Connector (Out)	RJ-45 x 1	
Housing	Plastic	Metal
Power Consumption (Max.)	DC 5V, 500mA	
Weight (g)	65g	182g
Dimensions H x W x D (mm)	23 x 47 x 85	22 x 52 x 80

▶ Connection Pattern



Features

- Extend USB signal transmission by using the existing LAN system without additional
- Unique Multi-users network configuration, negotiable controlling access setting
- Support full-duples and half-duplex operation
- Suitable for most of popular USB devices (e.g. USB sticks, USB printers, USB Scanner, external hard disk drives etc.)
- Up to 4 Units can be daisy chained and connected to an Ethernet Hub at a time
- Small profile for convenient installation and
- Easy to get and install the standard cable at lower cost
- Fully support Windows 2000 SP4, Windows XP SP2 or SP3, Windows Vista SP1/SP2, Windows 7 32-bit and 64-bit editions

