




KVMA switch to share Video and USB between multiple sources

ADDERView 4PRO-DVI-MS

Ultimate flexibility for sharing high-res screens and USB peripherals

PRODUCT IN BRIEF

The AV4PRO-DVI-MS is designed to enable four multihead computers to be controlled from a single high resolution KVM console using either dual link DVI or high definition analogue video links. The switch makes use of Adder's True Emulation technology which enables USB HID devices to be continuously emulated to each computer. This unique technology enables instantaneous and reliable hotkey switching whilst also supporting the extra keys and features of enhanced keyboards and mice. Furthermore, the AdderView includes two independently switchable USB 2.0 channels and an audio channel, giving the user the flexibility to attach selected peripherals to different computers. Models are available supporting single, dual, triple or quad head DVI or VGA computers.



FEATURES

High Definition VGA with extended profile DDC EDID

The AdderView Pro Multi Screen features full dual link DVI video delivering 4 megapixel resolutions per head at 60Hz. Because the AdderView features DVI-I, you can also use a choice of digital or analogue sources. The extended DDC EDID profile ensures that the switched graphics card is always optimised to work with your screen. The dual link DVI capabilities enable users to work at very high resolutions including 2K (2048 × 1080) on each head for post production or WQXGA (2560 × 1600) per head for detailed medical imaging.

True Emulation USB2.0 technology

The AV4PRO-DVI-MS belongs to the first KVMA range of switches to feature Adder's advanced True USB Emulation technology. Emulated USB provides an instantaneous and reliable switching action and makes keyboard hotkey and mouse switching possible. Previous implementations have used generic emulations and consequently have only been able to support the most basic keyboard and mouse features. Adder's revolutionary True Emulation technology overcomes this frustrating limitation by emulating the true character of the connected devices to all the computers simultaneously. This means that you can now use the extra function keys, wheels, buttons and controls that are commonly found on modern keyboards and mice.

Independent simultaneous device selection

Flexibility is key to the AdderView Pro.The switch enables you to use the KVMA console to work on one computer whilst your USB peripherals are connected to other computers and your speakers are playing music from

yet another. You can of course still switch all connected devices to any one of the connected computers as with any other KVM switch.

Channel selection options

PHO.

The AdderView Pro can be switched using selectable keyboard hotkeys, 3 button mice or the front panel controls. Optionally, you can also use the RC4 remote switch to make your selection. These switching options allow you to rapidly reasign connected devices to any of the connected computers.

Broad USB 2.0 Hi Speed device support

A vast range of USB devices can be connected to the AdderView Pro, from non standard human interface devices to printers and scanners. This gives great flexibility. For example, you could be scanning a set of documents onto one computer whilst working on another and printing from yet another, all at the same time. The USB 2.0 switching action has been carefully engineered to ensure maximum computer reliability when connecting and disconnecting USB devices.

Options port for control, synchronisation and upgrade

An 'Options' port enables the AV4PRO-DVI-MS to be remotely switched using simple ASCII codes. When the channel is switched, the same ASCII codes are echoed to the 'Options' port and so, by linking 'Options' ports, two or more units can be switched in synchrony to switch more than 4 video heads. The port enables a 4 button switch unit (RC4) to be used with the AdderView Pro. The same port can also be used to upgrade the firmware to guarantee that your hardware investment continues to deliver real value well into the future.

ADDERView 4PRO-DVI-MS

Ultimate flexibility for sharing high-res screens and USB peripherals

ABOUT ADDER

Adder is a leading developer and thought leader in connectivity solutions. Adder's advanced range of KVM switches, extenders and IP solutions enable the control of local. remote and global IT systems across the enterprise. The company distributes its products in more than 60 countries through a network of distributors, resellers and OEMs. Adder has offices in the United States, United Kingdom, Germany, the Netherlands, Sweden, China and Singapore.

To find out more, visit: http://www.adder.com.

RELATED PRODUCTS

Adder offer a vast range of products to suit your needs. Other products you may be interested in include:

ADDERView PRO AV4PRO-DVI



ADDERView PRO AV8PRO-DVI



SmartView MutiScreen SVMS2DVI-DUAL:







TECHNICAL SPECIFICATIONS

Hardware compatibility

All computers with USB interfaces

Software compatibility

Operates with all known software and operating systems including Windows (all), DOS, Linux, Unix, BSD, all Sun OS, all Mac OS, NetWare etc.

Computer connections at switch

USB2.0 type B, Dual-link DVI-I (up to 4 per connection), 3.5mm stereo jack

Local KVM console connection

- Video: Dual-link DVI-I (Dual x 2, Triple x $3 \text{ or Quad } \times 4$
- Keyboard/Mouse: 2 x USB type A
- Switched USB: 2 x USB2.0 type A Switched USB: Supports USB 2.0 devices in low, full and high speed modes.
- · Audio: 3.5mm stereo jack
- Other Connections: Options (flash upgrade, sync with other AV4PRO-DVI-MS and RS232 triggered power switches): Modular IOPIOC

Physical design

2.5U high metal case 26mm (w), 15mm (d), 10mm (h)

ORDERING INFORMATION

Dual version: AV4-PRO-DVI-DUAL-XX Triple version: AV4-PRO-DVI-TRIPLE-XX Quad version: AV4-PRO-DVI-QUAD-XX

= Mains Lead Country Code: UK = United Kingdom US = United States FURO = Europe AUS = Australia

ADDITIONAL ACCESSORIES

Rack Mount Kit:RMK5PROMS DVI to VGA adaptor: VSAII Single link DVI-D to DVI-D Video cable: VSCDI Audio cable 2 m :VSC22 Combined dual link DVI-D and USB cable: VSCD3 (2m): VSCD4 (5m) Flash upgrade adapter plus standard 3 m patch lead:

RC4 remote control plus standard 3 m patch cable: RC4-8P8C

Power connection

2.5mm DC jack (power adapter included), 100-240VAC 50/60Hz input to power adapter, 5VDC 2A output from power adapter

Operating temperature

0°C to 40°C / 32°F to 104°F

Approvals CE. FCC

