



Introduction

The Atlona **AT-HDVS-CAM** is an enterprise-grade PTZ camera designed for use with the AT-UHD-HDVS-300-KIT in soft codec conferencing applications. It features a USB interface for video and camera control. The HDVS-CAM seamlessly integrates with the HDVS-300-KIT for a complete, automated conferencing system that includes AV and USB extension, plus automatic input selection and display powering when a PC is connected. The HDVS-CAM delivers high performance, professional-quality imaging with video resolutions up to 1080p @ 30 Hz, as well as fast and accurate auto-focusing, and a fast yet quiet pan and tilt mechanism. This PTZ camera is ideal for a wide range of small to medium-sized meeting spaces, classrooms, and training rooms.


Applications

- **Meeting spaces and conference rooms**
The HDVS-CAM works together with the USB extension capability of the HDVS-300 system to enable simple, clean connectivity from the front wall to PCs at the meeting table.
- **Classrooms and other instructional spaces**
The HDVS-CAM is ideal for distance learning and collaboration, as well as lecture capture.

Key Features

- Designed for soft codec applications with the HDVS-300 system
- Also available as part of an AT-UHD-HDVS-300-C-KIT system package
- USB 2.0 interface for video and camera control
- Universal PC compatibility through standard UVC (USB Video Class) driver
- Compatible with a wide range of soft codecs and unified communications (UC) platforms
- High performance imaging, fine detail, and color rendering with 1/2.8" low-noise, HD CMOS sensor
- Available video resolutions from 176x144 up to 1080p @ 30 Hz
- Fast and accurate auto focus, plus auto white balance and auto exposure modes
- Fast and quiet pan and tilt mechanism
- Multi-element zoom lens with 10x optical zoom and a 60.9° horizontal field of view
- Picture controls available for brightness, color, saturation, contrast, sharpness, and gamma
- TCP/IP, RS-232, USB, and IR control – convenient handheld IR remote control included
- PTZ camera control available from popular soft codec and UC clients such as Skype® for Business
- Easy, GUI-based configuration using integrated web server
- Configured and managed by AMS (Atlona Management System)
- Award-winning 10 year limited product warranty

Connection Diagram



Specifications

Video		
HD/SD/VESA (all resolutions are @30/25/20/15/10/5Hz)	1080p, 720p, 1680x896, 1024x768, 1024x576, 960x540, 800x600, 640x360, 720x576, 640x480, 352x288, 320x240, 320x180, 176x144	
Optical Zoom	10X, f = 4.7 ~ 47 mm	
Viewing Angle	6.43° (telephoto), 60.9° (wide-angle)	
AV	F1.6 - F3.0	
Minimum Illumination	0.5 lm, F1.8 with Automatic Gain Control ON	
Video Compression	H.264, H.265	
Control Protocol	VISCA/Pelco-D/Pelco-P	
Network Protocol	RTSP/RTMP, ONVIF	
Pan Rotation	±170°	
Tilt Rotation	-30° ~ ±90°	
Pan Control Speed	0.1 - 180° / sec	
Tilt Control Speed	0.1 - 80° / sec	
Temperature		
Operating	Fahrenheit	Celsius
Storage		
Operating Humidity (RH)		
Storage Humidity (RH)		
Power		
Consumption		
Supply		
Dimensions		
H x W x D	Inches	Millimeters
Weight	Pounds	Kilograms
Device		
Certification		
Device		