

COMBINATION D-SUB CONTACTS

Coaxial contacts – Straight – PCB termination – 3 solder pins



RoHS compliant – CSA listed, File No.: LR 115000-1–UL listed, File No.: E 228329


DESCRIPTION

- 50 and 75 Ω design
- Contact finishings:
 - .051 μ " / 1.3 μ m Au mating side inner conductor /
 - .032 μ " / 0.8 μ m Au outer conductor
 - .008 μ " / 0.2 μ m Au mating side inner- and outer conductor
- Quality class 1: 500 mating cycles (gold plated)


PRODUCT DRAWING

50 Ω version


Socket contact



Installation dimension





Plug contact




75 Ω version

Socket contact



Plug contact



ORDER DATA

SOCKET CONTACT .051 μ " / 1.3 μ m Au INNER / .032 μ " / 0.8 μ m Au OUTER CONDUCTOR

Contact type	Termination*	Part Number
Socket 50 Ω	76	132 J 24019 X
Socket 75 Ω	86	132 J 34019 X

PLUG CONTACT .051 μ " / 1.3 μ m Au INNER / .032 μ " / 0.8 μ m Au OUTER CONDUCTOR

Contact type	Termination*	Part Number
Plug 50 Ω	76	131 J 24019 X
Plug 75 Ω	86	131 J 34019 X

SOCKET CONTACT .008 μ " / 0.2 μ m Au INNER- AND OUTER CONDUCTOR

Contact type	Termination*	Part Number
Socket 50 Ω	G7	132 A 24019 X
Socket 75 Ω	G8	132 A 34019 X

PLUG CONTACT .008 μ " / 0.2 μ m Au INNER- AND OUTER CONDUCTOR

Contact type	Termination*	Part Number
Plug 50 Ω	G7	131 A 24019 X
Plug 75 Ω	G8	131 A 34019 X

*Code use with constructor