


3107A Multi-Conductor - EIA Industrial RS-485 PLTC/CM



For more Information
please call

1-800-Belden1



Description

22 AWG stranded (7x30) tinned copper conductors, Datalene® insulation, twisted pairs, overall Beldfoil® shield (100% coverage) plus a tinned copper braid (90% coverage), drain wire, UV resistant PVC jacket.

Physical Characteristics (Overall):

Conductor:

AWG

# Pairs	AWG	Stranding	Conductor Material	Dia. (mm)
2.000	22	7x30	TC - Tinned Copper	0.762

Insulation:

Insulation Material

Insulation Trade Name	Insulation Material
Datalene®	FHDPE - Foam High Density Polyethylene

Outer Shield:

Outer Shield Material

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	90

Outer Shield Drain Wire AWG

AWG	Stranding	Drain Wire Conductor Material
22	7x30	TC - Tinned Copper

Outer Shield Drain Wire Diameter .030

Outer Jacket:

Outer Jacket Material

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cabling:

Overall Cabling Color Code Chart

Number	Color
1	White/Blue Stripe & Blue/White Stripe
2	White/Orange Stripe & Orange/White Stripe

Overall Nominal Diameter: 10.516 x 0.000 mm

Mechanical Characteristics (Overall):

Operating Temperature Range -20°C To +60°C

Non-UL Temperature Rating 60°C

Bulk Cable Weight: 108.639 Kg/Km

Max. Recommended Pulling Tension: 355.856 N

Min. Bend Radius (Install)/Minor Axis: 104.140 mm

Applicable Specifications and Agency Compliance (Overall):

Applicable Standards:

NEC/(UL) Specification CM, PLTC OIL RES II

3107A Multi-Conductor - EIA Industrial RS-485 PLTC/CM

CEC/C(UL) Specification	CM
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy)	10/01/2005

Flame Test:

UL Flame Test	UL1685 UL Loading
CSA Flame Test	FT1

Suitability:

Sunlight Resistance	Yes
---------------------	-----

Plenum/Non-Plenum:

Plenum (Y/N)	N
--------------	---

Electrical Characteristics (Overall):

Nom. Characteristic Impedance

Impedance (Ohm)
120.000

Nom. Capacitance Conductor to Conductor

Capacitance (pF/m)
36.091

Nom. Capacitance Cond. to Other Conductor & Shield

Capacitance (pF/m)
68.573

Nominal Velocity of Propagation

VP (%)
78

Nom. Conductor DC Resistance

DCR @ 20°C (Ohm/km)
48.231

Nominal Outer Shield DC Resistance

DCR @ 20°C (Ohm/km)
5.906

Nom. Attenuation

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Attenuation (dB/100m)
	1.000			1.641

Max. Operating Voltage - UL

Voltage
300 V RMS

Max. Recommended Current

Current
2.7 Amps per conductor @ 25°C

Input/Unfitted Impedance

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Impedance (Ohm)
	1.000			

Notes (Overall):

Notes Oil Resistance: Passes Oil Res II Per UL1277, Table 10.17. For CPE jacketed version order YR46792.

PUT UPS AND COLORS:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
3107A 0101000	305 MT	34.927 KG	BLACK	C	2 PR #22 FHDPE SH PVC BLK

3107A Multi-Conductor - EIA Industrial RS-485 PLTC/CM

3107A 0104000	1,219 MT	150.593 KG	BLACK	C	2 PR #22 FHDPE SH PVC BLK
3107A 0105000	1,524 MT	192.778 KG	BLACK	C N	2 PR #22 FHDPE SH PVC BLK

Notes:

C = CRATE REEL PUT-UP.

N = FINAL PUT-UP LENGTH MAY VARY -0% TO +10% FROM LENGTH SHOWN.

Revision Number: 1 Revision Date: 03-18-2008

© 2007 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory; and China Ministry of Information Industry order#39 (China RoHS). EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.