


AvediaStream Encoders

avstr-e3830-std



AvediaStream e3830 Standard Encoder

Standard HDMI encoder which delivers HD or SD H.264 streams from an HDMI video input over your existing network, including sources such as digital cameras, digital signage systems and PCs.



Interfaces

- Video Input
 - HDMI interface
- Audio Input
 - HDMI (Embedded PCM)
- 802.3 10/100/1000BaseT Ethernet (RJ-45 chassis socket)
- Serial RS232 Port for local admin (RJ-45 chassis socket)
- IR Out (3.5mm jack socket)

Streaming

- Single program MPEG-2 transport stream (ISO/IEC 13818-1)
- UDP
- RTP
- IP unicast
- IP multicast
- IGMP Join Group for enhanced switch compatibility

Channel Management

- Channel announcement via SAP/SDP
- Multicast/unicast address selection (automatic/manual)
- Configurable name, number and group membership

Management

- Configurable using Exterity management tools:
 - Admin level management using AvediaServer AvediaCare application
 - HTTPS device web interface; recommended browser: Chrome®
- SSDP device discovery
- RESTful API
- Serial RS232 Admin Port
- Event logging via Syslog (local and remote)

Video Input

- Automatic detection of resolution and frame rate
- Resolutions supported:
 - 1080p 23.98Hz/24Hz/50Hz/59.94Hz/60Hz
 - 1080i 50Hz/59.94Hz/60Hz
 - 720p 50Hz/59.94Hz/60Hz
 - 480p/525p 59.94Hz & 576p/625p 50Hz
 - 480i/525i 59.94Hz & 576i/625i 50Hz
- HD 16:9 aspect ratio
- SD 16:9 aspect ratio

Video Encoding

- MPEG-4 part 10 H.264 (ISO/IEC 14496-10)
 - Main Profile @ Level 4
- Video resolution: 525i, 525p, 625i, 625p, 720p, 1080i, 1080p
- Bit rate: 2Mbps – 25Mbps
- Frame rate: 23.98Hz/24Hz/50Hz/59.94Hz/60Hz

Audio Encoding

- AAC
- Encoding bit rate 48kbps – 512kbps
- Audio sampling rate 48kHz

Network

- Linux dual IPv4 stack
- DHCP or Static IP addressing
- 1000BASE-T, 100BASE-TX and 10BASE-T (802.3ab, 802.3u and 802.3 respectively)

Protocols

IP (RFC 791), UDP (RFC 768), TCP (RFC 793), ARP (RFC 826), DNS (RFC 1035), DHCP (RFC 2131), ICMP (RFC 792), IGMP (RFC 3376), Syslog (RFC 3164), NTP (RFC 1305), SAP (RFC 2974), SDP (RFC 4566), RTP (RFC 3550)

Regulatory

- CE:
 - IEC 62368-1:2014
 - EN62368-1:2014 + A11:2017
 - EN55032:2012 + corrigenda Aug 2012 & Dec 2012
 - EN55024:2010 + A1:2015
 - EN 61000-3-2:2014
 - EN 61000-3-3:2013
- UL/CSA:
 - UL62368-1/CSA C22.2 No. 62368-1, Rev. February 17, 2012
- FCC:
 - 47CFR:2011 Part 15, Sub Part B
 - ANSI C63-4:2014
- ACMA:
 - AS/NZS 62368:2018
 - AS/NZS CISPR 32: 2015

Physical Format

- Modular hot swap blade for Exterity chassis
- AvediaStream c1101 providing 1 inputs
- AvediaStream c1103 providing up to 3 inputs
- AvediaStream c1210 providing up to 10 inputs

Environment

- Operating: 0 ...+40°C / +32 ... +104°F
- Storage: -20 ...+70°C / -4 ... +158°F
- Operating and storage Relative Humidity: 10-90% (non-condensing)

Dimensions

- L: 275mm x W: 130mm x H: 40mm; weight 0.5kg

Power

- DC 24V: 10W typical, 25W maximum

MTBF

- Calculated to MIL-HDBK-217F, notice 2: 79421 hours (9.1 years)