AvediaStream g4130



The AvediaStream g4130 TVgateway distributes live terrestrial TV channels over your existing building, campus or wide area IP network.

- Streams all radio and TV channels from two DVB-T multiplexes per blade for lower cost per channel
- Streams both SD and HD channels
- Hot-swap capability for quick, non-intrusive upgrades
- Easy setup



Technical Specifications

Tuners

Two DVB-T tuners 2 x 75 ohm IEC aerial input (1 per tuner)

Control User Interface

DVB scan control
Stream specific channels from selected multiplex
Automatic or manual multicast address selection
Configure name, number, group membership per channel
Optional forwarding of EPG, EIT and other services
Stream on boot

Channel Streaming

Up to 80Mbps output per blade Single program MPEG transport streams RTP or UDP IP multicast or unicast Channel announcement using SAP/SDP

Network Interfaces

802.3 10/100BaseT Ethernet

Network Protocols

TCP, UDP, DHCP (client), IGMP

Management

SNMP, TFTP, HTTP Web management interface Serial console port

Chassis Options

AvediaStream c1101 providing 2 inputs AvediaStream c1103 providing up to 6 inputs AvediaStream c1110 providing up to 20 inputs

Power Consumption

15W Typical (18W Max)

For more information on our TVgateway solutions please refer to:

- TVgateway Family Product Brochure
- TVgateway Technical Specifications Datasheets g4135, g4150, g4155, g4170, g4190, g4210, g4215, g4230 and g4235
- Chassis Technical Specifications Datasheets c1101, c1103 and c1110

Head Office: Ridge Way, Hillend Industrial Park, Dalgety Bay, Dunfermline, UK, KY11 9JD

t: +44(0) 1383 828 250 f: +44(0) 1383 824 905 w: www.exterity.com e: info@exterity.com



g4130 Blade

Chassis







Resolution



