



KC-1300



Intelligent Media Converter Center Chassis

Product Highlights:

- Supports 16 slots for hot-plug converters
- 19" rack mountable
- Supports 90-264VAC and -48VDC power
- Power redundancy design
- Management
 - In-band console support
 - Web-based management
 - SNMP management
 - Telnet management
 - SNMP trapP

KC-300D



KC-300DM



KC-1300 Intelligent Media Converter Center Chassis provides 16 slots for standalone media converters. A variety of optional media converts is provided and includes Gigabit copper to fiber and Fast Ethernet copper to fiber.

The chassis provides centered power supply to the installed media converters and serves as a converter center and wiring concentrator. The power system is featured with power redundancy for commercial AC and DC power input. For easy monitoring the media converter operation in each slot, KC-1300 also provides many network management interfaces including in-band console, telnet, web browsing, SNMP, and event SNMP trap for different application needs.

Key Features:

- Managed Media Converter Center with 19-inch rack-mountable 2U chassis
- Managed system accommodates up to 16 media converters
- Highly modularized chassis design with
 - modular media converters
 - modular management module
 - two system power modules for power redundancy
- Provides high availability and maintainability
- Power backup (dual power inputs) featured with two power chassis
- Visible system status indication
- Supports in-band Telnet, SNMP and web-based management
- Supports out-of-band direct console management
- Management from anywhere and any platform using a web browser
- Easy-to-use point and click user interface
- Photographic quality interface to configure and monitor the system
- Supports in-band event SNMP trap report
- TFTP Software Upgrade

Optional Media Converters

- Gigabit copper to Gigabit fiber converter
- Tri-speed 10/100/1000 copper to Gigabit fiber converter series
- 10/100 Fast Ethernet Copper to Fast Ethernet fiber converter series



KGC-300



KGC-310, KGC-310M



Ordering Information:

Chassis	Slots	Managed	Power
KC-1300L-1A	16	None	1 AC
KC-1300L-2A	16	None	2 AC
KC-1300-1A	16	Yes	1 AC
KC-1300-2A	16	Yes	2 AC
KC-1300L-1D	16	None	1 DC
KC-1300L-2D	16	None	2 DC
KC-1300-1D	16	Yes	1 DC
KC-1300-2D	16	Yes	2 DC



FCC Part 15, Class A
CISPR 22 Class A

Katron Technologies Inc.

15F-7, No. 79, Sec. 1, Hsin Tai Wu Rd., Hsi-chih, Taipei Hsien, Taiwan.
Tel: 886-2-2698-3878
Fax: 886-2-2698-3873
E-mail: kti@ktinet.com.tw
URL: http://www.ktinete.com.tw

KTI Networks Inc.

7400 Harwin Dr., Suite 120 Houston, Texas
77036 U.S.A.
Tel: 713-266-3891
Fax: 713-914-0555
E-mail: kti@ktinet.com
URL: http://www.ktinete.com

Trademarks: All brand names are trademarks or registered trademarks of their respective holders.
This information is subject to change without prior notice.

Specifications :

System Model	KC-1300-1A	KC-1300-2A	KC-1300-1D	KC-1300-2D
Management	Managed	Managed	Managed	Managed
LEDs	Power1 , Power2 , CPU status, Fan status, Console Rx status, port link status			
System Model	KC-1300L-1A	KC-1300L-2A	KC-1300L-1D	KC-1300L-2D
Management	Unmanaged	Unmanaged	Unmanaged	Unmanaged
Number of Power	1 AC power	2 AC power	1 DC power	2 DC power
Input Voltage	90-264VAC	90-264VAC	-48VDC	-48VDC
Power Supply	60W	60W	60W	60W
19" Rack Mount	Yes	Yes	Yes	Yes
Number of MC Slots	16	16	16	16

Mechanical :

Chassis Height (2U)	88mm	88mm	88mm	88mm
Dimension	443x88x300 mm	443x88x300 mm	443x88x300 mm	443x88x300 mm
Weight	5.5kg	6.2kg	5.5kg	6.2kg
(with 1 or 2 AC power, management module and no MC converters)				

Environmental :

Operating Temperature -5°C ~ 40°C

Storage Temperature -20°C ~ 80°C

Relative Humidity 5%~95% non-condensing

Approval FCC class A, CE class A

Information of Optional Standalone Media Converters :

KC-300D	10/100Base-TX to 100Base-FX media converter series
KC-300DM	10/100Base-TX to 100Base-FX media converter series with remote loopback test and remote TP link monitoring functions
KGC-300	1000Base-T to 1000Base-X media converter series
KGC-310	10/100/1000Base-T to 1000Base-X media converter series with remote loopback test and remote TP link monitoring functions
KGC-310M	Web Smart 10/100/1000Base-T to 1000Base-X media converter series with remote loopback test, remote TP link monitoring functions and web-based management