

EL4500 KVM Extender

Dual Mode — DVI, Audio, and USB 2.0



The dual mode EL4500 KVM Extender, powered by ExtremeLink™ Technology, allows the user to position a computer remotely from the work area over a single Cat 5 (or better) cable or connection over a Local Area Network (LAN) using Rapid Pairing Protocol™ for easy, plug and play installation.

Applications include security, medical, interactive digital signage and industrial environments where the computer must be remotely accessible.

Key Product Features

- **HD Video:** 1680 x 1050 resolution, 24-bit color depth. Resolution does not degrade with distance.
- **Direct Connect:** Directly connect the local extender to the remote extender using a single Cat 5 (or better) cable up to 330 ft (100m). This mode of operation is ideal for installations requiring USB 2.0 up to 480Mbps.
- **Rapid Pairing Protocol™:** Allows for connection on a LAN or through a network switch. The system can be utilized on virtually any Ethernet network since it operates at Layer 2 and uses MAC addresses. There is no additional overhead or setup since it doesn't use the TCP/IP layer and typical network usage can be as low as 50Mbps.
- **Audio:** Integrated two channel audio with microphone and headphone I/O.
- **OS Support:** Compatible with all major operating systems. No drivers required.
- **Installation Ease:** True plug and play (no set up required). Utilizes a single Cat 5 (or better) cable for desktop extension simplifying installation.
- **Rack Mountable:** Allows for up to two units to be mounted in a 19"/1U rack mount kit.



Specifications subject to change without notification.

©2010

Icron Technologies Corp.
#90-00844-A02

EL4500 Specifications



Specifications subject to change
without notification.
©2011
Icron Technologies Corp.
#90-00844-A02

VIDEO PERFORMANCE

Video:	1680 x 1050 resolution, 24-bit color depth
Video Latency:	Less than 60ms
Reach:	LAN - With Rapid Pairing Protocol™ WAN (Wide Area Network) not supported 330ft (100m) Direct Connect
Interconnection Cable:	Standard solid core Cat 5 (or better) cable

LOCAL EXTENDER

Video:	DVI-D Video Input (24-pin connector)
USB:	1 x USB Type B
Dimensions:	4.4" x 6.9" x 1.18" (112mm x 175mm x 30mm)
Power:	5V, 3A DC (15W)

REMOTE EXTENDER

Video/Audio:	DVI-D Video Output (24-pin connector)
Audio:	3.5mm microphone in, 3.5mm headphone out
USB:	3 x USB Type A
Dimensions:	4.4" x 6.9" x 1.18" (112mm x 175mm x 30mm)
Power:	24V, 1A DC (24W)

ENVIRONMENTAL

Operating Temperature:	32°F to 122°F (0°C to 50°C)
Storage Temperature:	-4°F to 158°F (-20°C to 70°C)
Operating Humidity:	+20% ~ 80% (non condensing)
Storage Humidity:	+10% ~ 90% (non condensing)

CERTIFICATIONS

EMC:	FCC, Class A, CE, ICES-003
Compliance:	RoHS

Ordering Information

PART NUMBER	NAME	DESCRIPTION
EL4500 systems include a Local Extender, a Remote Extender, a USB cable, a DVI cable and two International power adapters with country specific power cord.		
00-00289	EL4500-NA	Dual Mode - DVI, USB 2.0 Extender System, 100-240V Power Adapter, NA plug
00-00290	EL4500-EU	Dual Mode - DVI, USB 2.0 Extender System, 100-240V Power Adapter, EU plug
00-00291	EL4500-UK	Dual Mode - DVI, USB 2.0 Extender System, 100-240V Power Adapter, UK plug
00-00292	EL4500-AU	Dual Mode - DVI, USB 2.0 Extender System, 100-240V Power Adapter, AU plug
00-00287	Rack Mount Adapter Kit	Four Brackets and Stencil (Screws not included)