


Flachsteckhülsen

Receptacles


Lötfreie Flachsteckhülsen ohne Isolation Solderless receptacles, non insulated



Material: CuZn blank oder verzinkt
CuSn blank oder verzinkt
Material: CuZn unplated or tin plated
CuSn unplated or tin plated

Artikel-Nummer Part number	ähnlich similar to DIN 46247	Leiter- querschnitt Wire size mm ² AWG	Steck- dicke Tab thickness mm	Abmessungen mm Dimensions mm		Verp.-Einhr. Stück Standard packing Piece
				L 1	L 2	
RS 7785.003 F 2,8-1	●	0,5-1 20-18	0,8	13,8	6,3	2000
RS 7785.002 F 2,8-1	●	0,5-1 20-18	0,5	13,8	6,3	2000
RS 7603 F 4,8-1	●	0,5-1 20-18	0,8	16	6,0	1000
RS 7603.001 F 4,8-1		0,5-1 20-18	0,5	16	6,0	1000
RS 7604 F 4,8-2,5	●	1-2,5 16-14	0,8	16	6,0	1000
RS 7604.001 F 4,8-2,5		1-2,5 16-14	0,5	16	6,0	1000
RS 7900 F 6,3-1	●	0,5-1 20-18	0,8	19	7,4	1000
RS 7901 F 6,3-2,5	●	1-2,5 16-14	0,8	19	7,4	1000
RS 8152 F 6,3-6	●	>2,5-6 12-10	0,8	19	7,4	1000
RS 7960.020 F 6,3-1 verriegelbar / self-locking	●	0,5-1 20-18	0,8	19,3	7,7	1000
RS 7961.020 F 6,3-2,5 verriegelbar / self-locking	●	>1-2,5 16-14	0,8	19,3	7,7	1000

Lötfreie Flachsteckhülsen ohne Isolation Solderless receptacles, non insulated



Material: CuZn blank oder verzinkt
CuSn blank oder verzinkt
Material: CuZn unplated or tin plated
CuSn unplated or tin plated

Artikel-Nummer Part number	ähnlich similar to DIN 46330	Leiter- querschnitt Wire size mm ² AWG	Steck- dicke Tab thickness mm	Abmessungen mm Dimensions mm		Verp.-Einhr. Stück Standard packing Piece
				L 1	L 2	
RS 7605 F 2,8-0,25		0,1-0,25 26-22	0,8	12,5	5,0	2000
RS 7605.001 F 2,8-0,25		0,1-0,25 26-22	0,5	12,5	5,0	2000
RS 7607 F 2,8-0,5		0,25-0,5 22	0,8	12,5	5,0	2000
RS 7607.001 F 2,8-0,5		0,25-0,5 22	0,5	12,5	5,0	2000
RS 7606 F 2,8-1	●	0,5-1 20-18	0,8	12,5	5,0	2000
RS 7606.001 F 2,8-1		0,5-1 20-18	0,5	12,5	5,0	2000