

1T-EDID-11 EDID/CEC Selector allows easy set up of the EDID and CEC parameters between a source and display monitor. Instead of waiting for the source and display to synchronize, this HDMI switcher saves time by using preset EDID and CEC settings to speed up the process. It's also easy to change your settings should that become necessary due to the selection of a different source or destination device or because you have purchased new equipment.

SD and HD video, RGB video and embedded audio parameters can all be selected via the front panel switches and button and system operation is displayed on an LED array. The product also features the unique TV One-task locking power connectors to enhance overall system mechanical security.

Specifications

Video Input

HDMI & DVI-D 1x via HDMI Connector, Type A

Video Outputs

HDMI 1x via HDMI Connector, Type A

Video Signal Proc.

Frequency Bandwidth 2.25Gbps

Standards Supported

HDMI, DVI (DVI via Cable Adapter)

Video Supported

SD and HD Formats 480i/p, 576i/p, 720p, 1080i/p

RGB Supported

DVI Equivalents VGA, SVGA, XGA, SXGA, UXGA

Audio Support

Dolby and LPCM TrueHD, DTS-HD, LPCM 7.1 & 2.0

Cable Distance

Max Distance For 1080p, 15m (50ft)

Environmental

Operating Temperature 0° to +40° C (+32° to +104° F)

Operating Humidity 20% to 90%, Non-condensing

Storage Temperature -10° to +60° C (+14° to +140° F)

Storage Humidity 20% to 90%, Non-condensing

Warranty

Limited Warranty 3 Years Parts and Labor

Regulatory Approvals

1T-EDID-11 FCC, CE, RoHS

Power Supply UL, CUL, CE, PSE, GS, RoHS

Mechanical (H-W-D)

1T-EDID-11 30x125x90mm (1.2x4.9x3.54")

Weight

1T-EDID-11 250g (0.55 lbs)

Power Requirement

External Power Supply 5 VDC@2A, Locking DC

Accessories Included

1x Power Adapter US, UK or Euro

1x User Manual

Model Numbers

1T-EDID-11 EDID/CEC Selector



Key Features of the 1T-EDID-11 Selector

- Compliant with HDMI v1.3 and DVI 1.0 standards
- Serial data rates of up to 2.25Gbps.
- Supports 12 bit Deep Color
- Selectable DTV Resolutions of 720p, 1080i/p
- Selectable PC resolutions of XGA, SXGA, UXGA
- Embedded audio: True HD, DTS-HD, LPCM
- Built in CEC support with Compliant CEC PHY
- HDMI Range of up to 15 Meters (50 ft)
- Locking DC Connectors for enhanced security

Panel Drawings

