## ewent

## Safety Data Sheet ISOPROPYL ALCOOL

#### Safety Data Sheet dated 20/12/2017, version 2

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification: Trade name: Model name:

ISOPROPYL ALCOOL SPRAY 200 ML EW5613

1.2. Relevant identified uses of the substance or mixture and uses advised against Recommended use: Technical product Uses advised against: do not use on humans and animals
1.3. Details of the supplier of the safety data sheet Company: ALBINA S.R.L. - Via Crocevia, 12 – 39057 – Appiano sulla strada del Vino (BZ) ALBINA S.R.L. – info@ewent-online.com
Competent person responsible for the safety data sheet:

info@ewent-online.com

#### **SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.

() Warning, Eye Irrit. 2, Causes serious eye irritation.

() Warning, STOT SE 3, May cause drowsiness or dizziness.

Adverse physicochemical, human health and environmental effects:

No other hazards 2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H222+H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None Contains

propan-2-ol; isopropyl alcohol; isopropanol

Special provisions according to Annex XVII of REACH and subsequent amendments: None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None Other Hazards:

section 10.3

#### **SECTION 3: Composition/information on ingredients**

- 3.1. Substances
- N.A.
- 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb	er	Classification
>= 70% - < 80%	propan-2-ol; isopropyl alcohol; isopropanol	Index number: CAS: EC:	603-117-00-0 67-63-0 200-661-7	<ul> <li>2.6/2 Flam. Liq. 2 H225</li> <li>3.3/2 Eye Irrit. 2 H319</li> <li>3.8/3 STOT SE 3 H336</li> </ul>
>= 15% - < 20%	GPL	CAS: EC: REACH No.:	68476-40-4 270-681-9 01- 2119486557- 22-XXXX	<ul> <li>2.5/C Compr. Gas H280</li> <li>2.2/1 Flam. Gas 1 H220</li> <li>DECLK (CLP)*</li> </ul>
>= 10% - < 12.5%	ethanol; ethyl alcohol	Index number: CAS: EC:	603-002-00-5 64-17-5 200-578-6	🚸 2.6/2 Flam. Liq. 2 H225

#### **SECTION 4: First aid measures**

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

- 4.2. Most important symptoms and effects, both acute and delayed Section 11
- 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Treatment:

Fellow the destart

Follow the doctor's instructions

#### **SECTION 5: Firefighting measures**

- 5.1. Extinguishing media
  - Suitable extinguishing media:
  - CO2 or Dry chemical fire extinguisher.
  - Extinguishing media which must not be used for safety reasons: Water jets.
- 5.2. Special hazards arising from the substance or mixture Do not inhale explosion and combustion gases. Burning produces heavy smoke.
- 5.3. Advice for firefighters
  - Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

#### **SECTION 6: Accidental release measures**

- 6.1. Personal precautions, protective equipment and emergency procedures Wear personal protection equipment.
  - Remove all sources of ignition.
  - Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

- 6.3. Methods and material for containment and cleaning up
  - Wash with plenty of water.
- 6.4. Reference to other sections See also section 8 and 13

#### **SECTION 7: Handling and storage**

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

- 7.2. Conditions for safe storage, including any incompatibilities
  - store in a cool, well ventilated place, away from heat, flames, sparks or other sources of ignition
    - keep only in the original container away from sunlight neighborhoods

avoid contact with skin and eyes, inhalation of vapours/mists/dusts.

do not use empty containers before they are cleaned.

contaminated clothing must be replaced before entering the dining areas.
at work do not eat or drink.
do not smoke
avoid the accumulation of electrostatic charges.
Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Cool and adequately ventilated.

7.3. Specific end use(s)

ideal product for cleaning electronic boards

#### **SECTION 8: Exposure controls/personal protection**

8.1. Control parameters propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0 ACGIH - TWA(8h): 200 ppm - STEL: 400 ppm - Notes: A4, BEI - Eye and URT irr, CNS impair ethanol; ethyl alcohol - CAS: 64-17-5 ACGIH - STEL: 1000 ppm - Notes: A3 - URT irr **DNEL Exposure Limit Values** N.A. **PNEC Exposure Limit Values** N.A. 8.2. Exposure controls Eye protection: Use close fitting safety goggles, don't use eye lens. Protection for skin: No special precaution must be adopted for normal use. Protection for hands: Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. Respiratory protection: Use adequate protective respiratory equipment. Thermal Hazards: Do not expose to temperatures exceeding 50° c. Environmental exposure controls: None Appropriate engineering controls: None

#### **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	colourless liquid		
Odour:	characteristic		
Odour threshold:	Not Relevant		
pH:	Not Relevant		
Melting point / freezing	<-40°C liquid		
point:	phase		

Initial boiling point and	>76°C liquid	 
boiling range:	phase	
Flash point:	< 0 ° C	 
	aerosol	
Evaporation rate:	Not Relevant	 
Solid/gas flammability:	Not Relevant	 
Upper/lower flammability	Not Relevant	 
or explosive limits:		
Vapour pressure:	5 bar +/- 1	 
Vapour density:	>2	 
Relative density:	0.800 kg/l +/-	 
	0.05	
Solubility in water:	partial	 
Solubility in oil:	complete	 
Partition coefficient (n-	Not Relevant	 
octanol/water):		
Auto-ignition temperature:	400°C (gas)	 
Decomposition	Not Relevant	 
temperature:		
Viscosity:	Not Relevant	 
Explosive properties:	section 10.3	 
Oxidizing properties:	Not Relevant	 

#### 9.2. Other information

Properties	Value	Method:	Notes:
kinematic viscosity:	kv > 2,05 mm2/s (a 40°C)		
Miscibility:	partial		
Fat Solubility:	complete		
Conductivity:	Not Relevant		
Substance Groups relevant properties	Not Relevant		

#### **SECTION 10: Stability and reactivity**

- 10.1. Reactivity
  - Stable under normal conditions
- 10.2. Chemical stability Stable under normal conditions
- 10.3. Possibility of hazardous reactions
  - may form explosive vapor / air mixtures in places not well ventilated
- 10.4. Conditions to avoid keep away from heat, sources of ignition avoid the accumulation of electrostatic charges.
  10.5. Incompatible materials
  - oxidizing agents
- 10.6. Hazardous decomposition products
  - the product is flammable, following combustion can lead to the formation of dangerous decomposition products by thermal decomposition can rid COx

#### **SECTION 11: Toxicological information**

11.1. Information on toxicological effects

Toxicological information of the product: N.A. Toxicological information of the main substances found in the product: propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0 a) acute toxicity: Test: LD50 - Route: Oral - Species: Rat > 5840 mg/kg Test: LD50 - Route: Skin - Species: Rat > 5840 mg/kg GPL - CAS: 68476-40-4 a) acute toxicity: Test: LC50 - Route: Inhalation - Species: Rat > 658 mg/l ethanol; ethyl alcohol - CAS: 64-17-5 LD50 (RABBIT) ORAL: 6300 MG/KG LD50 (RAT) ORAL SINGLE DOSE: 7060 MG/KG

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

a) acute toxicity;

b) skin corrosion/irritation;

c) serious eye damage/irritation;

d) respiratory or skin sensitisation;

e) germ cell mutagenicity;

f) carcinogenicity;

g) reproductive toxicity;

h) STOT-single exposure;

i) STOT-repeated exposure;

j) aspiration hazard.

#### **SECTION 12: Ecological information**

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment. propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48 Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 72 Endpoint: EC50 - Species: Fish > 100 mg/l - Duration h: 48

GPL - CAS: 68476-40-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish Negative 19 mg/l - Duration h: 96 Endpoint: LC50 - Species: Daphnia Negative 14.2 mg/l - Duration h: 48 Endpoint: EC50 - Species: Algae Negative 7.7 mg/l - Duration h: 96

12.2. Persistence and degradability

None

N.A.

- 12.3. Bioaccumulative potential
  - N.A.
- 12.4. Mobility in soil

N.A.

- 12.5. Results of PBT and vPvB assessment vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects None
- **SECTION 13: Disposal considerations**

13.1. Waste treatment methods

# Safety Data Sheet

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force. Additional disposal information:

contaminated packaging should be sent for recovery or disposal in compliance with national regulations on waste management

reuse if possible. Product residues are to be considered hazardous waste. disposal must be entrusted to authorised waste management, in compliance with national and, where appropriate, local.

#### **SECTION 14: Transport information**

14.1. UN number	
ADR-UN number:	1950
IATA-Un number:	1950
IMDG-Un number:	1950
14.2. UN proper shipping name	
14.3. Transport hazard class(es)	
ADR-Class:	2.5°F CAP. 2.2.2.1.6 UN1950
IATA-Class:	2.1
IMDG-Class:	2 Aerosols UN 1950
14.4. Packing group	
14.5. Environmental hazards	
Marine pollutant:	No
14.6. Special precautions for user	
IMDG-Page:	2102
14.7. Transport in bulk according to A	nnex II of Marpol and the IBC Code

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code No

#### **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 98/24/EC (Risks related to chemical agents at work) Dir. 2000/39/EC (Occupational exposure limit values) Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP) Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013 Regulation (EU) 2015/830 Regulation (EU) n. 286/2011 (ATP 2 CLP) Regulation (EU) n. 618/2012 (ATP 3 CLP) Regulation (EU) n. 487/2013 (ATP 4 CLP) Regulation (EU) n. 944/2013 (ATP 5 CLP) Regulation (EU) n. 605/2014 (ATP 6 CLP) Regulation (EU) n. 2015/1221 (ATP 7 CLP) Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications: None Where applicable, refer to the following regulatory provisions : Directive 2012/18/EU (Seveso III) Regulation (EC) nr 648/2004 (detergents). Dir. 2004/42/EC (VOC directive) Provisions related to directive EU 2012/18 (Seveso III): Seveso III category according to Annex 1, part 1 Product belongs to category: P3a

15.2. Chemical safety assessment No Chemical Safety Assessment has been carried out for the mixture.

#### **SECTION 16: Other information**

Text of phrases referred to under heading 3:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H280 Contains gas under pressure; may explode if heated.

H220 Extremely flammable gas.

Hazard class and	Code	Description
hazard category		
Flam. Gas 1	2.2/1	Flammable gas, Category 1
Aerosols 1	2.3/1	Aerosol, Category 1
Compr. Gas	2.5/C	Compressed gas
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure,
		Category 3

Paragraphs modified from the previous revision:

SECTION 2: Hazards identification SECTION 3: Composition/information on ingredients SECTION 4: First aid measures SECTION 8: Exposure controls/personal protection SECTION 9: Physical and chemical properties SECTION 10: Stability and reactivity SECTION 11: Toxicological information SECTION 13: Disposal considerations SECTION 15: Regulatory information SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Aerosols 1, H222+H229	On basis of test data
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H336	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

Society).CLP:Classification, Labeling, Packaging.DNEL:Derived No Effect Level.EINECS:European Inventory of Existing Commercial Chemical Substances.GefStoffVO:Ordinance on Hazardous Substances, Germany.GHS:Globally Harmonized System of Classification and Labeling of Chemicals.
DNEL:Derived No Effect Level.EINECS:European Inventory of Existing Commercial Chemical Substances.GefStoffVO:Ordinance on Hazardous Substances, Germany.GHS:Globally Harmonized System of Classification and Labeling of
GefStoffVO:Ordinance on Hazardous Substances, Germany.GHS:Globally Harmonized System of Classification and Labeling of
GHS: Globally Harmonized System of Classification and Labeling of
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.
KSt: Explosion coefficient.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
PNEC: Predicted No Effect Concentration.
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWA: Time-weighted average
WGK: German Water Hazard Class.